

NASA TECHNICAL NOTE



NASA TN D-6228

10
C.1

LOAN COPY: RETUR
AFWL (DOGL)
KIRTLAND AFB, NM

7 EEE10



TECH LIBRARY KAFB, NM

NASA TN D-6228

COMPUTER PROGRAM FOR THERMAL ANALYSIS OF TANK-MOUNTED MULTILAYER INSULATION

by Glenn R. Cowgill and William R. Johnson

Lewis Research Center
Cleveland, Ohio 44135

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION • WASHINGTON, D. C. • MAY 1971



0133037

1. Report No. NASA TN D-6228	2. Government Accession No.	3. Recipient's	
4. Title and Subtitle COMPUTER PROGRAM FOR THERMAL ANALYSIS OF TANK-MOUNTED MULTILAYER INSULATION	5. Report Date May 1971	6. Performing Organization Code	
7. Author(s) Glenn R. Cowgill and William R. Johnson	8. Performing Organization Report No. E-5911	10. Work Unit No. 129-04	
9. Performing Organization Name and Address Lewis Research Center National Aeronautics and Space Administration Cleveland, Ohio 44135	11. Contract or Grant No.	13. Type of Report and Period Covered Technical Note	
12. Sponsoring Agency Name and Address National Aeronautics and Space Administration Washington, D.C. 20546	14. Sponsoring Agency Code		
15. Supplementary Notes			
16. Abstract An analysis was done on the space-hold thermal performance of various multilayer insulation configurations on an oblate spheroidal tank. The thermal code CINDA-3G (Chrysler Improved Numerical Differentiating Analyzer for Third Generation Computers) was used for the thermal analysis, and several subroutines were written to tailor it for the needs of the problem. A portion of the tailoring is called the pre-preprocessor, which generates the data required as input to CINDA-3G. This pre-preprocessor and allied subroutines comprise a package to obtain a parametric thermal study with a minimum amount of input data. Parameters may be changed with a minimum of effort.			
17. Key Words (Suggested by Author(s)) IBM 7094 computer Computer programs Heat transfer	18. Distribution Statement Unclassified - unlimited		
19. Security Classif. (of this report) Unclassified	20. Security Classif. (of this page) Unclassified	21. No. of Pages 62	22. Price* \$3.00



CONTENTS

	Page
SUMMARY	1
INTRODUCTION	1
ANALYSIS	3
Thermal Model	3
Thermal Radiation	3
Computer Program - General	4
Finite Difference Equations.	4
Geometric Radiation View Factors Between Surfaces on a Flat Surfaced Payload and a Spheroidal Tank	8
DESCRIPTION OF SUBROUTINES	16
Pre-preprocessor Phase	16
Preprocessor Phase	17
Execution Phase.	17
APPENDIXES	
A - COMPUTER PROGRAM SYMBOLS.	20
B - FLOW DIAGRAM	25
C - DECK SETUP	26
D - TAPE USAGE	27
E - DESCRIPTION AND FORMAT OF INPUT DATA TO PRE-PROCESSOR	29
F - INPUT DATA FOR SAMPLE PROBLEM	31
G - FORTRAN LISTING OF AUTHOR-WRITTEN SUBROUTINES	34
H - SYMBOLS USED IN ANALYSIS	54
REFERENCES	57

COMPUTER PROGRAM FOR THERMAL ANALYSIS OF TANK-MOUNTED MULTILAYER INSULATION

by Glenn R. Cowgill and William R. Johnson

Lewis Research Center

SUMMARY

A computer program was developed to analyze the space-hold thermal performance of various multilayer insulation (MLI) configurations on the upper half of an oblate spheroidal liquid-hydrogen tank. The thermal model considered was an unshrouded tank within a hypothetical sun-oriented vehicle such that the payload was the only heat source in the system.

The thermal code CINDA-3G (Chrysler Improved Numerical Differencing Analyzer for Third Generation Computers) was chosen for the basic thermal analysis, and several subroutines were written to tailor it for the needs of the particular problem. A portion of the tailoring included a program called the pre-preprocessor, which generated the data required as input for the CINDA-3G program.

This pre-preprocessor and allied subroutines comprise a package to obtain a parametric thermal analysis of any multilayer covering on a spheroid. As a result, a minimum amount of input is required to specify the model geometry so that perturbations in the geometry configuration may be introduced with a minimum of effort.

INTRODUCTION

The long-term storage of liquid hydrogen in space can be effectively accomplished by using high-performance multilayer insulation (MLI) systems. A typical system would use a large number of highly reflective shields (aluminized polyester film) separated by low-thermal-conductivity spacers (e.g., silk netting).

A cross-sectional view of a sun-oriented vehicle with an unshrouded liquid-hydrogen tank covered with MLI is shown in figure 1. The payload intercepts all solar energy and thus represents the only high-temperature heat source in the vehicle. The direction of the anticipated heat flows could be as indicated by the arrows in figure 1. The only heat

being transferred into any of the tanks is through the MLI on the top half of the liquid-hydrogen tank. Therefore, this discussion will consider the thermal performance of the MLI on the top half of the liquid-hydrogen tank only.

This analysis will be general for a steady-state study of any oblate spheroidal tank and payload geometry. However, to simplify the discussion, the programs herein will be described with respect to a particular problem; that is, a steady-state analysis of a variable-thickness shield of MLI on the top half of an oblate spheroidal tank viewing a constant-temperature payload. A complete discussion and the results of this problem for the geometries considered may be found in reference 1.

A cross-sectional view of the variable-thickness MLI system on the top half of the liquid-hydrogen tank is shown in figure 2. The net heat flow by thermal radiation into the top surface of the MLI is transferred within the MLI by

- (1) Conduction in the lateral direction parallel to the shields, Q_{lat}
- (2) Combination of radiation and conduction in the normal direction perpendicular to the shields, Q_{norm}

For a steady-state condition to exist, the net thermal radiation received by the top surface of the MLI must be exactly equal to the total heat transferred through the MLI and into the liquid-hydrogen tank. The problem then becomes one of solving for the net heat flows after temperatures resulting from local heat balances throughout the MLI have been established.

There are a number of computer programs available which, when fed the proper input data to describe the model of a physical problem, will perform a thermal analysis and output the temperature distribution. When these programs are used, both building the mathematical model which describes the physical geometry and the preparation of the necessary input data are most tedious. To alleviate this difficulty, the computer subroutines described in this report were written to provide a ready means to generate this input data.

These subroutines are specifically designed to solve the problem described in reference 1, but can be generally applied to any tank in the shape of an oblate spheroid with layers of material covering the tank, or for a shell of varying thickness having the same general shape. These computer programs, then, generate the data required by CINDA-3G (ref. 2), which is the particular thermal analysis program chosen by the authors because of its versatility. The capability to readily effect small changes in geometry added to the versatility and afforded a substantial saving in time and effort.

The routines to be described herein are (1) a pre-preprocessor which takes the input data and converts it to the CINDA-3G data as prescribed by that program, (2) a view factor program which computes the geometric view factors for radiation in an enclosure, (3) an output routine which graphically displays the temperatures, thus making it easier to get an overall view of the temperature distribution, and (4) various other subroutines that are used for special operations by routines (1), (2), and (3).

ANALYSIS

Thermal Model

The thermal model for this problem is shown in figures 3 and 4. It consists of a 45° wedge of the MLI on top of an oblate spheroidal tank. This wedge is divided into a number of internal nodes.

For convenience, the geometry of all the nodes in a given column is assumed to be identical in the normal direction, having numerical values for the node width, node length, the lateral cross-sectional area (ALAT), and the normal area (ANORM) based on the dimensions on the top surface of the MLI. This should introduce no significant error when the maximum MLI thickness is small relative to the minor tank radius.

The node length for each segment (column) is described by specifying the angles $\theta_1, \theta_2, \dots, \theta_n$ (all θ 's must be integers). The depth of all nodes is constant and is specified by two input variables: the number of shields in each node, NSPL, and the thickness of each shield, DELS. The product of NSPL and DELS then is the depth of each internal node. The number of nodes in each column is an input variable, NL, which is a function of the MLI thickness being simulated in that particular column. The program is set up to accept a maximum of 30 segments and up to 50 nodes in each column. For the particular problem under discussion, 10 segments were used with varying numbers of layers (see fig. 3). The computed performance of this wedge is then multiplied by 8 to obtain the results for the entire top half of the tank.

A constant-value boundary node represents the temperature of the tank and the tank surface is held at this constant temperature. The payload is simulated by a flat disk divided into concentric rings (maximum, 10 rings). Space is simulated by a constant-temperature node with temperature at absolute zero and an emissivity equal to unity (blackbody).

Thermal Radiation

An enclosure composed of the payload, the surface of the MLI, and an imaginary surface representing space is used to compute the net thermal radiation received by the top surface of the MLI. The enclosure formed with the various surfaces labeled is shown in figure 5. The enclosure used in this discussion is composed of the 10 tank surface areas, five payload surface areas, and an imaginary surface simulating space, for a total of 16 surfaces.

The payload surface represented by a flat disk is divided into concentric rings of approximately equal area (labeled A_{11} to A_{15} in fig. 5). Each of these rings is consid-

ered to be a separate surface of the enclosure, and as such, each ring may have a different surface emissivity and a different constant temperature which is considered to be an infinite heat source. This is then assumed to be a multiple gray surface enclosure and simulates a radiosity network. A CINDA-3G subroutine, IRRAD1, is then used to compute the net radiant heat flow rates to each surface of the enclosure. Subroutine IRRAD1 uses a method described in reference 3 to obtain the net radiant heat flow to each surface.

Computer Program - General

CINDA-3G is a two-pass or double-phase operation consisting of a preprocessor phase and an execution phase. The user input data (description of the model) to CINDA-3G are converted into FORTRAN IV language subroutines by the preprocessor. These subroutines are then passed onto the system FORTRAN compiler for compilation and execution for solution of the problem.

Since the user input data as described in reference 2 are for a fixed geometric model, much extra labor would be necessary to change the input for a slightly modified geometry. Thus, a set of subroutines were written to accept a general description of the model and to generate the user input data so that the geometry can easily be varied by small changes in input data. This set of author-written subroutines was added to the CINDA-3G system as an additional phase of operation, making a three-pass or three-phase operation. This additional phase, called the pre-preprocessor, is executed first to generate all the necessary input data as required by the CINDA-3G preprocessor using a minimum amount of punched card input data. The CINDA-3G data are described in reference 2 (pp. 4. 1 to 4. 21). Control is then passed to the CINDA-3G preprocessor (phase 2) to process this generated data and to generate the subroutines for the third phase of the operation to perform the execution of the problem.

Because of this method of combining the three phases of operation and the use of certain portions of the computer operating system, this overall program as described is usable only on IBM 7094 II/7044 Direct Couple Systems running under the operating system IBSYS version 13, with a FORTRAN IV compiler. However, the CINDA-3G program is available for other computer configurations, for example UNIVAC 1108; and the routines written by the authors as described in this report could easily be modified to operate on these other computers since they are entirely written in FORTRAN IV.

Finite Difference Equations

The input to CINDA-3G is the description of the model. This description is given by

designating each incremental volume, called a node, by a number and then describing the heat paths between nodes by specifying the node numbers of the two adjoining nodes and a value which represents the conductance between these two nodes. Conductance is the area of heat flow times the thermal conductivity divided by the conductor length. Heat flow to boundaries is specified by supplying heat-transfer coefficients or radiation constants as the conductance between the two nodes.

When a network (model) to the problem has been described, the solution is obtained by solving a set of finite difference equations, which are an approximation to the partial differential equations of the diffusion type

$$\frac{\partial T}{\partial t} = \alpha \nabla^2 T + S \quad (1)$$

where T is temperature, t is time, α is diffusivity

$$\alpha = \frac{k}{C_p} \quad (2)$$

∇^2 is the Laplacian operator in x , y , z coordinates, and S is a source term defined as

$$S = \frac{\dot{q}\alpha}{k} \quad (3)$$

where \dot{q} is heat rate per unit volume and k is thermal conductivity.

Since we are interested in only the steady-state solution for this particular problem, the time derivative is equal to zero, and equation (1) reduces to Poisson's equation:

$$\alpha \nabla^2 T + S = 0 \quad (4)$$

Substituting equations (2) and (3) into equation (4) results in

$$\frac{k \nabla^2 T}{\rho C_p} + \frac{\dot{q}k}{k \rho C_p} = 0 \quad (5)$$

Then since ρC_p may be assumed to be a constant for steady-state computation, multiply both sides of equation (5) by ρC_p to get

$$k\nabla^2 T + \dot{q} = k \left(\frac{\partial^2 T}{\partial x^2} + \frac{\partial^2 T}{\partial y^2} + \frac{\partial^2 T}{\partial z^2} \right) + \dot{q} = 0 \quad (6)$$

Then

$$k\nabla^2 T + \dot{q} \approx \frac{k}{\Delta x} \left(\frac{\partial T}{\partial x^-} - \frac{\partial T}{\partial x^+} \right) + \frac{k}{\Delta y} \left(\frac{\partial T}{\partial y^-} - \frac{\partial T}{\partial y^+} \right) + \frac{k}{\Delta z} \left(\frac{\partial T}{\partial z^-} - \frac{\partial T}{\partial z^+} \right) + \dot{q} \quad (7)$$

where the plus and minus signs in the first partial term indicate that they are taken on the negative or positive side, respectively, of the point under consideration. If three consecutive points (1, 0, and 2) ascending in the x direction are considered, the finite difference of the x portion of equation (7) is

$$\frac{k}{\Delta x} \left(\frac{\partial T_0}{\partial x^-} - \frac{\partial T_0}{\partial x^+} \right) \approx \frac{k}{\Delta x} \left(\frac{T_1 - T_0}{\Delta x^-} + \frac{T_2 - T_0}{\Delta x^+} \right) \quad (8)$$


applying this to equation (7) for x , y , and z for the points

1, 0, 2 in x direction

3, 0, 4 in y direction

5, 0, 6 in z direction

yields:



$$k\nabla^2 T_0 + \dot{q} = \frac{k}{\Delta x} \left(\frac{T_1 - T_0}{\Delta x^-} + \frac{T_2 - T_0}{\Delta x^+} \right) + \frac{k}{\Delta y} \left(\frac{T_3 - T_0}{\Delta y^-} + \frac{T_4 - T_0}{\Delta y^+} \right) + \frac{k}{\Delta z} \left(\frac{T_5 - T_0}{\Delta z^-} + \frac{T_6 - T_0}{\Delta z^+} \right) + \dot{q} \quad (9)$$

taking common denominator of volume $V = (\Delta x)(\Delta y)(\Delta z)$ and $A_x^- = (\Delta y)(\Delta z)$, $A_y^- = (\Delta x)(\Delta z)$, $A_z^- = (\Delta x)(\Delta y)$ and combining equation (9) with equation (6) to obtain

$$\begin{aligned} \frac{kA_x^-}{\Delta x^-}(T_1 - T_0) + \frac{kA_x^+}{\Delta x^+}(T_2 - T_0) + \frac{kA_y^-}{\Delta y^-}(T_3 - T_0) + \frac{kA_y^+}{\Delta y^+}(T_4 - T_0) + \frac{kA_z^-}{\Delta z^-}(T_5 - T_0) \\ + \frac{kA_z^+}{\Delta z^+}(T_6 - T_0) + \dot{q} = 0 \end{aligned} \quad (10)$$

now let $G_1 = kA_x^-/\Delta x^-$, $G_2 = kA_x^+/\Delta x^+$, $G_3 = kA_y^-/\Delta y^-$, . . . , etc. Then

$$\begin{aligned} G_1(T_1 - T_0) + G_2(T_2 - T_0) + G_3(T_3 - T_0) + G_4(T_4 - T_0) + G_5(T_5 - T_0) \\ + G_6(T_6 - T_0) + \dot{q} = 0 \end{aligned} \quad (11)$$

$$\begin{aligned} G_1 T_1 + G_2 T_2 + G_3 T_3 + G_4 T_4 + G_5 T_5 + G_6 T_6 + \dot{q} \\ = T_0(G_1 + G_2 + G_3 + G_4 + G_5 + G_6) \end{aligned} \quad (12)$$

or

$$T_0 = \frac{G_1 T_1 + G_2 T_2 + G_3 T_3 + G_4 T_4 + G_5 T_5 + G_6 T_6 + \dot{q}}{G_1 + G_2 + G_3 + G_4 + G_5 + G_6} \quad (13)$$

or, in more general terms,


$$T_0 = \frac{\sum G_i T_i + \dot{q}_0}{\sum G_i} \quad (14)$$

where i ranges over all neighboring nodes to T_0 .

Since all the temperatures T_i in equation (14) are not known, assume some initial temperatures and solve this equation for T_0 ; when this is done over all the nodes in the network, a new temperature distribution will be obtained. Iterate in this fashion with equation (14) over all the nodes in the network until the temperatures obtained do not change between two consecutive iterations by more than some prescribed value, called the convergence criterion. This is the method used by the execution routine CINDSS (see ref. 2).

Geometric Radiation View Factors Between Surfaces on a Flat-Surfaced Payload and a Spheroidal Tank

The geometric radiation view factor between any two surfaces A_i and A_j shown in the following sketch is defined by equation (15)



(b)

$$A_i F_{i,j} = \int_{A_i} \int_{A_j} \frac{\cos \varphi_i \cos \varphi_j dA_i dA_j}{\pi R^2} \quad (15)$$

where $F_{i,j}$ represents the portion of the total energy, either emitted or reflected by surface i , that is intercepted by surface j . As shown in the sketch, φ_i and φ_j are the angles between the respective normals to the surface elements dA_i and dA_j and the connecting line R .

The double integral in equation (15) is approximated by the following double summation in order to obtain a numerical solution on the digital computer:

$$A_i F_{i,j} = \sum_{A_i} \sum_{A_j} \frac{\cos \varphi_i \cos \varphi_j \Delta A_i \Delta A_j}{\pi R^2} \quad (16)$$

The radiosity subroutine used to calculate the net heat into each surface of the enclosure requires the following numerical input:

A_{NE} area of each surface in the enclosure

T_{NE} temperature of each surface in the enclosure

ϵ_{NE} emissivity of each surface in the enclosure

$A \times F$ area times geometric view factor for each interchange in the enclosure (see ref. 2, p. 6.6.2)

The procedure described in this section first determines the individual values of $A \times F$ for each of the tank surfaces viewing each of the payload surfaces. Once these primary values are determined, all other values of $A \times F$ are readily determined. The equations used to define the other values of $A \times F$ are discussed at the very end of this section.

The view factors, and subsequently the net q into each of the surfaces in the radiosity enclosure, are computed for the entire top half of the tank and the entire payload. As described earlier, in the discussion of the model, the top node of each column of MLI is a 45° segment. These segments are extended completely around the tank to form a ring and the net q is computed for each of these rings. These q 's are then divided by 8 to obtain the net q into each node on top of the MLI. The method of computing the view factors described herein further breaks up each of these rings on the MLI and also breaks up the payload surfaces, described on page 3, into smaller rings. Then these small areas with their respective view factors are added together to obtain the $A \times F$ for each payload surface and each MLI surface, where each MLI surface is a ring as described previously.

The actual view factors are calculated as follows: The payload is arbitrarily divided into concentric rings each having a width of 0.1 foot (3.05 cm). Each ring with area A_p is then further divided into incremental areas ΔA_p . As shown in figure 6, the subscript p will pertain to the payload surface, and the subscript t will pertain to the tank surface. The number of incremental areas in each ring N_J is varied so that the numerical value of ΔA_p remains approximately constant over the entire payload. Thus, for the payload ring shown in figure 6, N_J is the nearest whole number determined by the following expression:

$$N_J = 20\pi R_p \quad (17)$$

The number of these rings of 0.1-foot (3.05-cm) width which are to be included in each of the individual payload surfaces is then readily determined.

The MLI surface on the tank is arbitrarily divided into 90 increments of 1° each, measured from the vertical z-axis. As shown in figure 6, the incremental area extends in a ring completely around the tank. The location of this ring is specified by ψ_m , the angular distance from the vertical z-axis. Each ring with area A_t is further divided into incremental areas ΔA_t of constant size over the entire tank surface. The number of individual rings to be included in each of the separate tank surfaces used in the enclosure is then readily determined once the angular size of each of the surfaces is specified.

The variable MLI thickness over any particular tank surface area is accounted for by reading in the number of nodes used at that particular location. The numerical values of a and b (the major and minor semi-axes of the spheroid formed by the surface of the MLI) are determined individually for each of the tank areas used.

$$a = X_r + \Delta S$$

$$b = Y_r + \Delta S$$

where ΔS is the thickness of the MLI and X_r and Y_r are the uninsulated tank dimensions. Thus for any particular surface area of the tank, the existing MLI thickness over that particular area is considered to exist over the entire tank surface.

Both the tank and the payload are symmetrical about their respective z-axes. Because of this symmetry and the fact that the z-axes of both coordinate systems coincide, the geometric view factor of any one element ΔA_t along a given tank ring to any given

complete payload ring is independent of position. Thus, equation (16) may be written in the following manner:

$$A_t F_{t,p} = A_t \sum_{A_p} \frac{\cos \varphi_t \cos \varphi_p \Delta A_p}{\pi R^2} \quad (19)$$

where A_t and A_p are the tank and payload ring areas, respectively. Thus, the view factor $F_{t,p}$ of any ring on the tank to any ring on the payload is the summation of the view factors to all the incremental areas making up the payload ring.

To simplify the geometry, the typical element ΔA_t on any given tank ring, selected to view all elements ΔA_p on any given payload ring, is located in the yz plane. In this plane, the equation of the MLI surface is

$$\frac{y^2}{a^2} + \frac{z^2}{b^2} = 1 \quad (20)$$

The following geometric relations are then valid:

$$\left. \begin{aligned} R_t &= ab \sqrt{\frac{1}{b^2 \sin^2 \psi_m + a^2 \cos^2 \psi_m}} \\ y_t &= R_t \sin \psi_m \\ z_t &= R_t \cos \psi_m \\ \Delta h &= b - z_t \end{aligned} \right\} \quad (21)$$

For each value of ψ_m used, the entire payload will be divided into incremental areas ΔA_p . Thus, R_p will be a function of the payload ring being considered, and γ_n will be a function of the location of ΔA_p . The following relations can be seen from figure 6:

$$\left. \begin{array}{l} x_p = R_p \cos \gamma_n \\ y_p = R_p \sin \gamma_n \\ \Delta A_p = \frac{\pi}{N_J} \left[\left(R_p + \frac{\Delta L}{2} \right)^2 - \left(R_p - \frac{\Delta L}{2} \right)^2 \right] \end{array} \right\} \quad (22)$$

where N_J is determined by equation (17). Differentiating equation (20) gives the slope at any point on the curve:

$$\frac{dz}{dy} = -\frac{b^2}{a^2} \frac{y}{z} \quad (23)$$

The slope of a line normal to that point m_{N_1} can be expressed as

$$m_{N_t} = -\frac{1}{\frac{dz}{dy}} = \frac{a^2}{b^2} \frac{z}{y} = \frac{a^2 z_t}{b^2 y_t} \quad (24)$$

where z_t and y_t are the coordinates of the point shown in figure 6. The vector \vec{N}_t representing the normal from this point is

$$\vec{N}_t = \hat{j} + m_{N_t} \hat{k} \quad (25)$$

and the unit vector \hat{N}_t becomes

$$\hat{N}_t = \frac{\hat{j} + m_{N_t} \hat{k}}{\sqrt{1 + m_{N_t}^2}} \quad (26)$$

Since the payload surface is in the xy plane,

$$\hat{N}_p = -\hat{k} \quad (27)$$

The vector $\vec{R}_{t,p}$ from ΔA_t to ΔA_p can be expressed as

$$\vec{R}_{t,p} = (x_p - x_t) \hat{i} + (y_p - y_t) \hat{j} + (z_p - z_t) \hat{k} \quad (28)$$

Since $x_t = 0$,

$$\vec{R}_{t,p} = x_p \hat{i} + (y_p - y_t) \hat{j} + (z_p - z_t) \hat{k} \quad (29)$$

$$R = \left| \sqrt{x_p^2 + (y_p - y_t)^2 + (z_p - z_t)^2} \right| \quad (30)$$

Thus the unit vector $\hat{R}_{t,p}$ becomes

$$\hat{R}_{t,p} = \frac{x_p \hat{i} + (y_p - y_t) \hat{j} + (z_p - z_t) \hat{k}}{R} \quad (31)$$

and


$$\hat{R}_{p,t} = -\hat{R}_{t,p} \quad (32)$$

The angles φ_t and φ_p can now be determined by forming scalar products:

$$\cos \varphi_t = \hat{N}_t \cdot \hat{R}_{t,p} = \frac{(y_p - y_t) + m_{N_t} (z_p - z_t)}{R \left| \sqrt{1 + m_{N_t}^2} \right|} \quad (33)$$

$$\cos \varphi_p = \hat{N}_p \cdot \hat{R}_{p,t} = \frac{z_p - z_t}{R}$$

The tank surface area A of any ring is determined with the equation obtained from the following derivation:



(c)

$$dA = 2\pi y \, ds$$

$$ds = \sqrt{(dy)^2 + (dz)^2}$$

$$\frac{y^2}{a^2} + \frac{z^2}{b^2} = 1$$

$$y = a \sqrt{1 - \frac{z^2}{b^2}}$$

$$dy = \frac{-az \, dz}{b^2 \sqrt{1 - \frac{z^2}{b^2}}}$$

$$\therefore dA = (2\pi) \left(a - \sqrt{1 - \frac{z^2}{b^2}} \right) \left[\sqrt{\frac{a^2 z^2}{b^4 \left(1 - \frac{z^2}{b^2} \right)}} + 1 \right] dz$$

$$\therefore dA = 2\pi a \left[\sqrt{1 + \left(\frac{a^2}{b^4} - \frac{1}{b^2} \right) z^2} \right] dz$$

$$\therefore A = 2\pi a \int_{z_i}^{z_{i+1}} \sqrt{1 + w_z^2} dz$$

where

$$w_z^2 = \frac{a^2}{b^4} - \frac{1}{b^2} = \frac{a^2 - b^2}{b^4}$$

Thus

$$A_p = 2\pi a \left[\frac{z}{2} \sqrt{1 + w_z^2} + \frac{1}{2w_z} \ln \left(zw_z + \sqrt{w_z^2 + 1} \right) \right]_{z_i}^{z_{i+1}} \quad (34)$$

Therefore all quantities required in equation (19) are determined.

To obtain the value of $A_m F_{m,n}$ between specific areas m and n is simply an appropriate summation of the results of equation (19):

$$A_m F_{m,n} = \sum_{\substack{\text{All tank} \\ \text{rings in the} \\ m^{\text{th}} \text{ segment}}} \sum_{\substack{\text{All payload} \\ \text{rings in the} \\ n^{\text{th}} \text{ segment}}} A_t F_{t,p} \quad (35)$$

All other values of $A_m F_{m,n}$ can now be generated using the following relations:

(1) Since no surface "sees" itself, $F_{m,m} = 0$ for any m .

(2) Since no two surfaces on the tank "see" each other, $F_{m,n} = 0$ for all tank surfaces m and n .

(3) Since no two surfaces on the payload "see" each other, $F_{m,n} = 0$ for all payload surfaces m and n .

(4) By definition, $\sum_{n=1}^{\text{All surfaces}} F_{m,n} = 1$.

(5) By reciprocity, $A_m F_{m,n} = A_n F_{n,m}$.

DESCRIPTION OF SUBROUTINES

As previously discussed, the program is divided into three phases: (1) the pre-preprocessor, which by using the input data described in appendix A of this report computes the input data needed to run a problem with CINDA-3G and generates a tape according to the formats given on pages 4.1 to 4.2 of reference 2; (2) the preprocessor, as described in reference 2; and (3) the execution phase, which actually computes the temperature distribution.

Pre-preprocessor Phase

The pre-preprocessor is composed of four subroutines which read data cards describing the geometry, compute the data required by the CINDA-3G system, and write this data onto a tape to be used in phase 2.

The subroutines in the pre-preprocessor are as follows:

Subroutine name	FORTRAN call name	Brief description
PREPRE	Main program	Reads the input data, computes the data required by CINDA-3G
VIEWFC	VIEWF	Computes the geometric view factors for the radiation interchange used in subroutine IRRAD1
RAYOUT	RITARY	Called by PREPRE; writes arrays of numbers onto the input tape as prescribed by CINDA-3G, p. 4.10 of ref. 2
COMDAT	BLOCK COMMON	Block common subroutine

Preprocessor Phase

The preprocessor is the second phase of the operation. A list of the subroutines and a description of each is given in reference 2 (pp. 8. 1 to 8. 3). The only variation is that the preprocessor reads the data from the tape that was prepared by the pre-preprocessor phase instead of from cards.

Execution Phase

The actual computing to determine the temperature distribution is done in the execution phase. In this execution phase the following subroutines are used: LINKO, EXECDK, VAR1DK, VAR2DK, OUTDK, which are generated by the preprocessor phase of CINDA-3G.

LINKO is the main program. Its only function is to call the INPUT routines to read in the CINDA input data and call EXECDK.

EXECDK is called the execution block of the program. It retains control until the problem is solved. Subroutines VAR1DK, VAR2DK, and OUTDK are called by EXECDK or by other subroutines called from EXECDK.

VAR1DK, VAR2DK, and OUTDK are the subroutines generated from the VARIABLES 1 block, VARIABLES 2 block, and OUTPUT block, respectively, that are described in reference 2. The order of calculation in the execution phase of the program is described, along with a flow chart, in reference 2 (pp. 3. 12 and 3. 13).

Several subroutines were written by the authors and incorporated into the execution phase in the user subroutine section. These subroutines may be easily modified or re-written by the user because they must be included into the program deck as FORTRAN source cards. The subroutines are

Subroutine name	FORTRAN call name
CNDCTR	GETG
OUTEND	ENDOUT
DISTR	TDIST
GRAFIC	PICTR
PUNTEM	PCHT

Subroutine CNDCTR computes the value of all internal conduction connectors G_i between two nodes i and j.

$$G_i = \frac{A_k}{l_{i,j}} \quad (36)$$

where

- A area of heat flow
- k thermal conductivity
- l distance from the center of node i to center of node j

If the thermal conductivity varies with temperature

$$G_i = \frac{A}{\frac{l_i}{k_i} + \frac{l_j}{k_j}} \quad (37)$$

where k_i and k_j are temperature-varying thermal conductivities at nodes i and j. These conductors are computed just prior to each iteration of the network solution.

Subroutine CNDCTR as listed in this report was written to permit the use of very high thermal conductivity shields (pure aluminum as opposed to aluminized mylar) to increase the lateral thermal conductivity of some layers of the MLI. The nodes in these layers with high conductivity will be denoted as hi-k nodes. All other interior nodes with a lower conductivity will be denoted as standard nodes. It should be noted that this is conduction in the lateral direction only. The thermal conductivity for the standard nodes is determined by straight-line curve fit. Input variables CON1 and CON2 are the a and b, respectively, for the line $k = aT + b$. The data for the hi-k nodes are input in a table with variable name AKVST. The format for this table is found in appendix E. For the data used in the sample problem for both the standard nodes and the hi-k nodes see figure 8 of reference 1. The thermal conductivity for conduction in the normal direction $k_{\text{effective}}$ is a combination of conduction and radiation (see ref. 1 for details). Subroutine CNDCTR also calls subroutine IRRAD1 to obtain the net Q into each surface of the radiosity enclosure.

Subroutine OUTEND calls subroutine GRAFIC and then computes and prints out the heating rates Q of the fuel tank to MLI, QNORM, and also the net heat into the MLI on the top surface of the MLI, QTS. QNORM and QTS are printed in tabular form to show the Q in or out of each segment on the tank. Further, these values are then multiplied by 8 to obtain the Q in and out for the entire tank. The names of these output variables are QN8 and QTS8. These printouts occur each time the print switch (NPRINT) calls for an output of the temperature distribution.

Subroutine TDIST reads the initial temperature distribution from tape unit SYSUT5 which was written in the pre-preprocessor.

Subroutine GRAFIC is a special subroutine which prints out the temperature distribution pictorially. Blocks are made, simulating the nodes, and are printed to simulate the shape of the shield. Inside each block is printed a node number and the temperature of that node. A node number with a minus sign in front denotes this node is a hi-k node, as described in the section on subroutine CNDCTR. If the top of the box is made up of dollar signs (\$\$\$\$\$\$) instead of asterisks (*****) it denotes a surface with a high surface emissivity (see sample output listing on p. 31).

Subroutine PUNTEM punches cards with the current temperatures if either the number of iteration loops or the amount of computer time requested on the TCP card is exceeded.

Lewis Research Center,
National Aeronautics and Space Administration,
Cleveland, Ohio, December 2, 1970,
129-04.

APPENDIX A

COMPUTER PROGRAM SYMBOLS

FORTRAN name	Corresponding mathematical symbol	Units in program	Description
A	A_{norm}	ft^2	Conduction area in normal direction
AFA	$A_i F_{ij}$	ft^2	Product of i^{th} surface area and the geometric view factor between i^{th} and j^{th} surfaces
AKVST	k	Btu/(hr)(ft)(°F)	Thermal conductivity table
ARCLN	---	ft	Arc length
AREAL	A_L	ft^2	Conduction area in lateral direction
BOTLIM	---	---	Integrand of equation (34) evaluated at lower limit z_i
BTA	β	deg	Angle measured from minor axis to segment boundary on tank
C	---	---	Array of user constants to CINDA-3G
CINCON	---	---	Array of control constants to CINDA-3G
CONNAM	---	---	Array of control constant names
CON1	---	---	Constant = a } a straight-line curve fit for k for lateral con-
CON2	---	---	Constant = b } duction; k = aT + b
DAMPA	---	---	Damping factor (CINDA control constant)
DAREA	A_t	ft^2	Incremental area on MLI for view factor computation

FORTRAN name	Corresponding mathematical symbol	Units in program	Description
DELDMP	---	---	Delta to add to change damping factor
DELS	---	ft	Thickness of each shield
DMLI	ΔS	ft	Thickness of MLI at a given segment
DPTH	---	ft	Thickness (depth) of each node
EMISP	ϵ	---	Emissivity of each surface of payload
EMISS	ϵ	---	Emissivity of space
EMIST	ϵ	---	Emissivity of each surface on MLI
G	G	Btu/(hr)($^{\circ}$ F)	Conductor value for heat transfer
H	h	ft	Tank-to-payload spacing
IEXECN	---	---	Name of CINDA execution routine to be used
LCK2	---	---	Tape unit SYSCK2 CINDA input written on
LUT3	---	---	Tape unit SYSUT3 used as temporary storage for FORTRAN subroutines to be used in execution phase
LUT5	---	---	Tape unit SYSUT5 initial temperatures stored on this unit, to be read in execution phase
MAXNL	---	---	Maximum number of nodes at any segment
NDAMP	---	---	Change damping factor every NDAMP iterations
NHIK	---	---	Number of high-conductivity layers


FORTRAN name	Corresponding mathematical symbol	Units in program	Description
NIN	---	---	Tape unit, input unit
NL	---	---	Number of nodes in MLI in normal direction for each segment
NNODES	---	---	Total number of nodes in configuration
NNPAY	---	---	Number of nodes on payload
NNSEG	---	---	Number of segments on tank
NOFA	---	---	Number of entries in view factor matrix
NOUT	---	---	Tape unit, output unit
NPAY	---	---	Same as NNPAY above
NPRINT	---	---	Print temperatures every NPRINT iterations
NSEG	---	---	Same as NNSEG above
NSPL	---	---	Number of shields in each node
NSTMTS	---	---	Number of FORTRAN cards read in as user program to go into SUBROUTINES block of CINDA-3G
NSURF	---	---	Number of surfaces in radiation enclosure
NTAB	---	---	Total number of entries in K-vs-T table (AKVST)
NUMHIK	---	---	Array containing layer numbers of high-conductivity layers
PSI	ψ_m	---	Angle from top of tank to R_1
QNORM	Q	Btu/hr	Heat flow from MLI into tank

FORTRAN name	Corresponding mathematical symbol	Units in program	Description
QTS	Q	Btu/hr	Heat flow from enclosure into top of MLI
R1	R_1	ft	Distance from tank center to incremental surface i
R1X	R_1	ft	Distance from tank center to incremental surface i + 1
RP	R_p	ft	Radius of payload
SLAY	---	---	Number of nodes in MLI in normal direction at each 1° increment
SPACEE	ϵ	---	Emissivity of space
TCARDS	---	---	Switch: If equal to zero, use temperatures input with input data; then distribute initial temperatures throughout configuration with subroutine TDIST. If not equal to zero, read initial temperature distribution from cards.
THETA	θ	deg	Array of angles specifying angular segments on tank
THIKN	---	---	Same as DPTH above
TPAY	T	°R	Array temperatures of payload nodes
TSPACE	T	°R	Temperature of space node
TSURF	T	°R	Initial temperature on MLI surface
TWALL	T	°R	Temperature of tank wall
UPLIM	---	---	Integrand of equation (34) evaluated at upper limit
X	X_r	ft	Major semi-axis of tank

FORTRAN name	Corresponding mathematical symbol	Units in program	Description
XM1	m_{N_1}	--	Slope
Y	Y_r	ft	Minor semi-axis of tank

APPENDIX B

FLOW DIAGRAM



APPENDIX C

DECK SETUP

The following is the deck setup to run this program at Lewis Research Center on the IBM 7094-7044 Direct Couple System using IBSYS version 13:

cc1	cc8	cc16
\$ID	JO	USER NAME
\$TCP		TIME=XX, PAGES=YY
\$SETUP	10	CIN3G
\$IBJOB		

[FORTRAN IV source or binary decks of pre-preprocessor as described in this report.
(Includes subroutines PREPRE, VIEWFC, RAYOUT, and COMDAT.)]

\$DATA

[FORTRAN IV source cards of user-written subroutines. For this problem these subroutines include CNDCTR, OUTEND, DISTRT, GRAFIC, and PUNTEM. Any other user-written subroutines may be added here.]

ENDX

[Input data as described in appendix E.]

\$IBSYS	
\$REWIND	SYSCK2
\$SWITCH	SYSIN1, SYSCK2

APPENDIX D

TAPE USAGE

Tape units must be made compatible between CINDA-3G and the computer system. A table of tape usage presently being used at Lewis Research Center only with the CINDA-3G program is included to aid in making this compatible with other systems.

SYSUNI name	FORTRAN number in CINDA-3G	Variable name in program	Lewis system number	Function
UT3	2	LUT3	14	Copy of original problem data
UT4	3	LUT4	15	Parameter change data*
UT8	4	LUT1	3	Data number definitions
IN1	5	NIN	5	Input
OU1	6	NOUT	6	Output
UT2	8	LUT2	13	NA-NB pairs, data number definitions for parameter changes
CK1	9	-----	10	CINDA-3G master tape
CK2	10	-----	16	New master tape if updating, also used as problem recall data tape*
UT5	11	-----	7	Problem store data tape*
UT6	12	LBD3	1	Data tape (original problem and all parameter changes)
PP1(LB4)	13	-----	Calcomp	System plot tape
LB3	14	LB4P	9	Program tape (contains generated FORTRAN routines; LINKO, EXECTN, VARBL1, VARBL2, OUTCAL)

SYSUNI name	FORTRAN number in CINDA-3G	Variable name in program	Lewis system number	Function
UT7	15	LUT7	2	Variables 1 calls generated from node and conductor data blocks*
UT9	16	-----	4	
UT9	99	-----	4	Internal file for reread
LB2	17	-----	8	Overlay tape

The tapes marked by an asterisk need not be assigned if the particular options are not used. The STOREP option in CINDA-3G requires assigning and saving tapes on units LB3 and UT5. The RECALL option requires assigning and mounting these two tapes onto units LB3 and CK2, respectively.

APPENDIX E

DESCRIPTION AND FORMAT OF INPUT DATA TO PRE-PREPROCESSOR

Input Data Description

CARD 1 FORMAT(I4, 2I3, 7F10.5)
NSEG NO. OF SEGMENTS (MAXIMUM 30)
NPAY NO. OF SURFACES, (SEGMENTS) ON PAYLOAD (MAXIMUM 10)
NSPL NO. OF SHIELDS PER LAYER
DELS THICKNESS OF EACH (SHIELD+SPACER) FT.
TWALL TEMPERATURE OF TANKWALL DEG.R
TSURF TEMPERATURE OF TOP SURFACE OF SHIELD DEG.R
TSPACE TEMPERATURE OF SPACE DEG.R
EMISS EMISIVITY USED IN EQUATION FOR K(EFF),
CONDUCTION IN NORMAL DIRECTION
SPACEE EMISIVITY OF SPACE
RP RADIUS OF PAYLOAD FT.

CARD 2 FORMAT(6F10.5, A6)
TCARDS SWITCH- TO READ INITIAL TEMPERATURES
IF TCARDS =0, CARDS WILL NOT BE READ. THE PROGRAM
USES TWALL AND TSURF AND DISTRIBUTES THE TEMPERATURES
BETWEEN THESE TWO VALUES AS THE INITIAL TEMPERATURE
DISTRIBUTION.
IF TCARDS .GT. 0 THE INITIAL TEMPERATURE DISTRIBUTION
IS READ FROM CARDS, (DEG. R). SEE CARDS 11 BELOW.
X LENGTH OF SEMI-AXIS OF ELIPSE, (TANKWALL),ALONG X AXIS
Y LENGTH OF SEMI-AXIS OF ELIPSE, (TANKWALL),ALONG Y AXIS
H TANK TO PAYLOAD SPACING FT.
CON1 CONSTANTS USED FOR STRAIGHT LINE CURVE FIT TO COMPUTE
CON2 THERMAL CONDUCTIVITY FOR G VALUES FOR LATERAL
CONDUCTION OF STANDARD NODES. K=CON1*T+CON2.
IEXECN NAME OF EXECUTION ROUTINE CINDSS OR CINDSL

CARD 3 FORMAT(2I10, F10.5)
NPRINT DELTA PRINT, PRINT TEMP. DIST. EVERY NPRINT ITERATIONS
NDAMP CHANG DAMPING FACTOR EVERY NDAMP ITERATIONS
DELDMP DELTA TO ADD TO DAMPING FACTOR

CARD 4 FORMAT(I8,9F8.3)
CINCON(I) CINDA CONTROL CONSTANTS, AS REQUIRED BY EXECUTION
ROUTINE BEING USED. CONSTANTS INPUT IN ORDER AS
FOLLOWS ACCORDING TO FORMAT GIVEN ABOVE,
NLOOP, ARLXCA, DAMPA, DRLXCA, DAMPD, TIMEO,
TIMEND, OUTPUT, DTIMEI, CSGFAC.

CARDS 5 NTAB, (AKVST(I),I=1,NTAB) FORMAT(I6,12F6.1/(6X,12F6.1))
TABLE OF TEMPERATURE VS. THERMAL CONDUCTIVITY FOR
LATERAL CONDUCTION OF HIGH CONDUCTIVITY LAYERS.
NTAB= TOTAL NO. OF ENTRIES IN TABLE (TEMPS AND K'S)
DATA FORM NTAB TEMP1 K1 TEMP2 K2 --- TEMPN KN
UNITS-- K BTU/HR-FT-DEG.R
T DEG.R

CARDS 6 NL NUMBER OF LAYERS IN EACH SEGMENT FORMAT (NI2)

APPENDIX F

INPUT DATA FOR SAMPLE PROBLEM

SHIELDING STUDY CONFIGURATION NO. 24										
10	5	5	.0016667	37.0	295.0	0.0	0.24	--	1.0	5.0
			4.571	3.233	0.8175	.000047	.0045	-	CINDESS	
	125		2000	0.1				-		
	9999		.0001	0.1				-		
104	37.	.8	40.	.873	45.	.913	50.	.970	55.	1.010
	62.	1.055	64.	1.065	66.	1.0875	68.	1.105	70.	1.112
	74.	1.116	75.	1.117	76.	1.116	78.	1.114	80.	1.112
	84.	1.090	86.	1.085	88.	1.072	90.	1.062	95.	1.040
	105.	.985	110.	.955	115.	.925	120.	.900	125.	.880
	135.	.837	140.	.819	145.	.800	150.	.785	155.	.770
	165.	.742	170.	.730	175.	.720	180.	.711	185.	.700
	195.	.687	200.	.683	205.	.675	210.	.672	215.	.668
	225.	.662	230.	.660	235.	.658	240.	.655	220.	.665
242223	0201717151311	8								
2715	9	9	6	6	4	4				
	.11		.11		.11		.11			
	520.0	520.0	520.0	520.0	520.0	520.0				
	.024		.024		.024		.024		.024	.900
	.900		.900							
	4	8	11	1315						

OUTPUT FOR SAMPLE PROBLEM

SHIELDING STUDY CONFIGURATION NO. 24

*****	*****
*	*
* PAYLOAD NODES	*
* NODE NOS	179 180 181 182 183 *
*	*
* TEMPS=	520.00 520.00 520.00 520.00 520.00 *
* EMISIV=	0.1100 0.1100 0.1100 0.1100 0.1100 *
*****	*****

*****	*****
*	*
* SPACE	*
* NODE NO.	184 *
*	*
* TEMP=	0. *
* EMISIV	1.0000 *
*****	*****

ANGLE OF EACH SEGMENT(DEG.)

27.0 15.0 9.0 9.0 6.0 6.0 6.0 4.0 4.0 4.0

EMISIVITY OF EACH SEGMENT

0.0240 0.0240 0.0240 0.0240 0.0240 0.0240 0.9000 0.9000 0.9000 0.9000

TANK TO PAYLOAD SPACING= 0.8175 FT.

LAYER NO.

*****	*****
24	* 25 * * 340.27*

23	* 24 * * 331.26*

22	* 23 * 48 * * 321.44* 317.63*

21	* 22 * 47 * * 310.72* 306.77*

20 • 21 • 46 • 69 • 90 •
• 298.88* 294.54* 286.25* 262.06*

19 • 20 • 45 • 68 • 89 *
• 285.58* 280.90* 272.16* 252.90*

18 • 19 • 44 * 67 • 88 •
• 270.27* 265.30* 256.60* 240.99*

17 • 18 • 43 • 66 • 87 * 108 • 126 *
• 252.02* 246.77* 238.48* 225.46* 215.58* 195.77*

16 • 17 • 42 • 65 • 86 * 107 • 125 •
• 228.92* 223.24* 215.80* 205.86* 197.55* 186.02*

15 • -16 * -41 * -64 • -85 • -106 • -124 • -142 •
• 195.88* 188.96* 183.10* 178.40* 173.98* 170.70* 167.44*

14 • 15 * 40 • 63 • 84 * 105 * 123 * 141 •
* 176.08* 170.70* 166.28* 162.63* 159.38* 156.82* 154.65*

13 • -14 • -39 • -62 • -83 • -104 • -122 • -140 • -156 •
• 146.57* 143.90* 141.98* 140.39* 138.87* 137.60* 136.23* 134.96*

12 • 13 * 38 • 61 • 82 • 103 • 121 • 139 * 155 •
• 131.96* 130.02* 128.59* 127.33* 126.17* 125.16* 124.16* 123.49*

11 • -12 • -37 • -60 • -81 • -102 • -120 • -138 • -154 • -168 •
• 110.36* 109.60* 108.99* 108.42* 107.84* 107.29* 106.67* 106.05* 105.40*

10 • 11 • 36 • 59 * 80 • 101 • 119 • 137 • 153 • 167 •
* 102.06* 101.46* 100.94* 100.45* 99.96* 99.51* 99.04* 98.65* 98.51*

9 • 10 * 35 • 58 • 79 • 100 • 118 • 136 • 152 • 166 •
• 91.32* 90.88* 90.47* 90.09* 89.72* 89.38* 89.04* 88.79* 88.72*

8 * -9 * -34 • -57 • -78 • -99 • -117 * -135 * -151 • -165 • -177 •
• 74.74* 74.55* 74.37* 74.18* 73.98* 73.76* 73.51* 73.20* 73.00* 72.81*

7 * 8 * 33 • 56 * 77 • 98 • 116 • 134 • 150 • 164 • 176 •
* 72.04* 71.89* 71.74* 71.60* 71.45* 71.31* 71.15* 71.08* 71.03* 70.99*

6 * 7 * 32 * 55 • 76 • 97 • 115 • 133 • 149 • 163 * 175 •
• 69.13* 69.02* 68.91* 68.80* 68.69* 68.65* 68.60* 68.57* 68.54* 68.53*

5 * 6 • 31 * 54 • 75 • 96 * 114 • 132 • 148 • 162 • 174 •
* 55.93* 65.85* 65.78* 65.71* 65.65* 65.63* 65.61* 65.60* 65.59* 65.58*

4 * 5 • 30 • 53 • 74 • 95 • 113 * 131 * 147 • 161 • 173 •
• 52.27* 62.22* 62.18* 62.14* 62.11* 62.10* 62.09* 62.08* 62.08* 62.08*

3 * 4 * 29 * 52 • 73 • 94 • 112 • 130 * 146 * 160 • 172 •
* 57.90* 57.87* 57.84* 57.83* 57.82* 57.81* 57.81* 57.80* 57.80* 57.80*

2 * 3 * 28 • 51 • 72 • 93 • 111 • 129 • 145 • 159 • 171 •
• 52.30* 52.28* 52.27* 52.26* 52.26* 52.26* 52.25* 52.25* 52.25* 52.25*

1 * 2 • 27 • 50 • 71 • 92 * 110 • 128 • 144 • 158 • 170 •
* 43.98* 43.97* 43.97* 43.97* 43.96* 43.96* 43.96* 43.96* 43.96* 43.96*

TANKWALL 1 26 49 70 91 109 127 143 157 169
SURFACE 37.00 37.00 37.00 37.00 37.00 37.00 37.00 37.00 37.00 37.00

* *
• TANKWALL *
• NODE NO.= 178 •
* TEMP.= 37.00 •
• *

SHIELDING STUDY CONFIGURATION NO. 24

NO. SEG	QTS	QNORM	QTS*8	QNORM*8
1	0.06936889	0.00018959	0.55495113	0.00151672
2	0.10318061	0.00029260	0.82544488	0.00234082
3	0.09149027	0.00025254	0.73192215	0.00202030
4	0.04330576	0.00032500	0.34644613	0.00260004
5	0.04622486	0.00023741	0.36979891	0.00189930
6	0.00980636	0.00027727	0.07845092	0.00221822
7	-0.20052147	0.00028314	-1.60417175	0.00226517
8	-0.09447652	0.00018922	-0.75581217	0.00151382
9	-0.04718843	0.00019050	-0.37750745	0.00152403
10	-0.01882567	0.00018001	-0.15060541	0.00144006
SUMMATION	0.23647E-02	0.24173E-02	0.18917E-01	0.19339E-01

APPENDIX G

FORTRAN LISTING OF AUTHOR-WRITTEN SUBROUTINES

\$IBFTC PREPRE

```

COMMON/BCD/ NBCD(60)                                1
COMMON /TAPE/NIN,NOUT,LCK2                           2
COMMON /RADIO/ NSEG,NPAY,NSURF,X,Y,H,RP,THIKN,PIE,SLAY(90), 3
1 THETAD(30),A(41),AFA(1681)                      4
DIMENSION ID(14),BTA(31),ERAD(31),THETA(30),F(30),ITEST(50),NL(30) 5
DIMENSION ARCLN(30),AREAL(30),NSNOD(30),NUMHIK(30),C(36)          6
DIMENSION AKVST(200), EMIST(41), TPAY(10), EMISP(10)                 7
DIMENSION ISTMT(14), T(1545), CONNAM(10), CINCON(10)                8
DIMENSION IFMT1(7), IFMT4(4), IFMTH(5)                     9
DIMENSION Z1(9),Z2(9),Z3(9),Z4(9),Z5(9),Z6(9),Z7(9),Z8(9)        10
DIMENSION Z9(9),Z10(9),Z11(9)                         11
EQUIVALENCE (NNSEG,C),(NNPAY,C(2)),(NSURFS,C(3)),(MNODES,C(4)), 12
X (MAXVL,C(5)),(NPRINT,C(6)),(NDAMP,C(7)),(NNL,C(8)),(NAREAL,C(9)), 13
X (NAREAN,C(10)),(NARCLN,C(11)),(NTHETA,C(12)),(NTEST,C(13)), 14
X (NKHIC,C(14)),(NEMISS,C(15)),(NAFA,C(16)),(NSNT,C(17)), 15
X (SIGMA,C(21)),(DPHT,C(22)),(DELS,C(23)),(EMISS,C(24)), 16
X (CON1,C(25)),(CON2,C(26)),(DELDMP,C(27)), 17
X (TABS,C(29)),(HIKCON,C(30)),(PSWTCH,C(31)),(RAD,C(32)) 18
X ,(HH,C(33))                                         19
DATA IFMT1(1)/ 42H(           I2/      F2.0/(10F8.5))      / 20
DATA IFMTH(1)/ 30H(7X,17HBCD 3THERMA      ,56X ) / 21
DATA CONNAM(1)/60H NLOOPARLXCA DAMPADRLXCA DAMPD TIMEOTIMENDOUTPUT 22
1DTIMEICSGFAC / 23
DATA ISL,IWBK,IBACK,IVARB,ISPS,ILPS,IENDX 24
1 /6HCINDSL,6HCNFWBK,6HCNBACK,6HCNVARB,6HL SPCS,6HL LPCS,6H ENDX / 25
DATA M1, ONE, ONEM, TEN20, PI, TABS, SIGMA 26
1 /1, 1.0, -1.0, 6H1.E+20, 3.14159265, 460.0, 0.173E-8 / 27
DATA 28
1 Z1(1)/ 54H NL, NO. OF LAYERS IN EACH SEGMENT / 29
2,Z2(1)/ 54H AREAL, AREA, LATENT CONDUCTION, EACH SEGMENT (HORIZ) / 30
3,Z3(1)/ 54H A, AREA, NORMAL CONDUCTION, EACH SEGMENT (VERT) / 31
4,Z4(1)/ 54H ARCLN, ARC LENGTH, LENGTHS FOR LATENT CONDUCTION / 32
5,Z5(1)/ 54H THETA (DEG.), ANGLE OF EACH SEGMENT / 33
6,Z6(1)/ 54H ITEST, NEGATIVE NO. IS HI-COND. LAYER, LATENT CONDCT/ 34
7,Z7(1)/ 54H AKVST, K(BTU/HR.FT) VS T(DEG R) FOR HI-K LAYERS / 35
8,Z8(1)/ 54H EMIST, EMISSIVITY OF SHIELD, RADIATION. / 36
9,Z9(1)/54H AF, AREA*VIEWFACTOR FOR RADIOSITY, FOR EACH SEGMENT / 37
A,Z10(1)/54H TABLE OF SURFACE NODE NUMBERS, SURFACE EACH SEGMENT / 38
PIE=PI
PIO4= PI/4.
NIN= 5
NOUT= 6
LUT3=2
LCK2=10
LUT5= 11
REWIND LCK2
REWIND LUT3
REWIND LUT5
DO 12 I=1,10
12 CINCON(I)=0.
C WRITE EXECUTE, ID, IBJOB CARDS, THEN ALL CINDA3G PREPROCESSOR 51
C                                         52

```

C	CARDS ONTO TAPE SYSCK2 (9)	53
C	WRITE(LCK2,2000)	54
C		55
C	READ PRE-PREPROCESSOR DATA AND GENERATE CINDA DATA	56
C		57
I=1		58
1	READ(NIN,2018) ISTM	59
	WRITE(LUT3) ISTM	60
	IF(ISTMT(2) .EQ. IENDX) GO TO 7	61
I= I+1		62
GO TO 1		63
7	NSTMTS= I	64
	REWIND LUT3	65
	READ(NIN,1000) ID	66
		67
		68
C	INPUT DATA DESCRIPTION	69
C CARD 1	FORMAT(I4, 2I3, 7F10.5)	70
C	NSEG NO. OF SEGMENTS (MAXIMUM 30)	71
C	NPAY NO. OF SURFACES, (SEGMENTS) ON PAYLOAD (MAXIMUM 10)	72
C	NSPL NO. OF SHIELDS PER LAYER	73
C	DELS THICKNESS OF EACH (SHIELD+SPACER) FT.	74
C	TWALL TEMPERATURE OF TANKWALL DEG.R	75
C	TSURF TEMPERATURE OF TOP SURFACE OF SHIELD DEG.R	76
C	TSPACE TEMPERATURE OF SPACE DEG.R	77
C	EMISS EMISIVITY USED IN EQUATION FOR K(EFF),	78
C	CONDUCTION IN NORMAL DIRECTION	79
C	SPACEE EMISIVITY OF SPACE	80
C	RP RADIUS OF PAYLOAD FT.	81
C		82
C		83
C CARD 2	FORMAT(6F10.5, A6)	84
C	TCARDS SWITCH- TO READ INITIAL TEMPERATURES	85
C	IF TCARDS =0, CARDS WILL NOT BE READ. THE PROGRAM	86
C	USES TWALL AND TSURF AND DISTRIBUTES THE TEMPERATURES	87
C	BETWEEN THESE TWO VALUES AS THE INITIAL TEMPERATURE	88
C	DISTRIBUTION.	89
C	IF TCARDS .GT. 0 THE INITIAL TEMPERATURE DISTRIBUTION	90
C	IS READ FROM CARDS. (DEG. R). SEE CARDS 11 BELOW.	91
C	X LENGTH OF SEMI-AXIS OF ELIPSE, (TANKWALL),ALONG X AXIS	92
C	Y LENGTH OF SEMI-AXIS OF ELIPSE, (TANKWALL),ALONG Y AXIS	93
C	H TANK TO PAYLOAD SPACING FT.	94
C	CON1 CONSTANTS USED FOR STRAIGHT LINE CURVE FIT TO COMPUTE	95
C	CON2 THERMAL CONDUCTIVITY FOR G VALUES FOR LATERAL	96
C	CON2 CONDUCTION OF STANDARD NODES. K=CON1*T+CON2.	97
C	IEXECN NAME OF EXECUTION ROUTINE CINDSS OR CINDSL	98
C CARD 3	FORMAT(2I10, F10.5)	99
C	NPPRINT DELTA PRINT, PRINT TEMP. DIST. EVERY NPRINT ITERATIONS	100
C	NDAMP CHANG DAMPING FACTOR EVERY NDAMP ITERATIONS	101
C	DELDMP DELTA TO ADD TO DAMPING FACTOR	102
C		103
C CARD 4	FORMAT(I8,9F8.3)	104
C	CINCON(I) CINDA CONTROL CONSTANTS, AS REQUIRED BY EXECUTION	105
C	ROUTINE BEING USED. CONSTANTS INPUT IN ORDER AS	106
C	FOLLOWS ACCORDING TO FORMAT GIVEN ABOVE,	107
C	NLOOP, ARLXCA, DAMPA, DRLXCA, DAMPD, TIMED,	108
C	TIMEND, OUTPUT, DTIMEI, CSGFAC.	109
C		110
C CARD 5	NTAB, (AKVST(I),I=1,NTAB) FORMAT(I6,12F6.1/(6X,12F6.1))	111
C	TABLE OF TEMPERATURE VS. THERMAL CONDUCTIVITY FOR	112
C	LATERAL CONDUCTION OF HIGH CONDUCTIVITY LAYERS.	113
C	NTAB= TOTAL NO. OF ENTRIES IN TABLE (TEMPS AND K'S)	114

```

C      DATA FORM   NTAB TEMP1      K1 TEMP2      K2 --- TEMPN  KN      115
C          UNITS-- K BTU/HR-FT-DEG.R      116
C          T DEG.R      117
C          118
C      CARDS 6 NL      NUMBER OF LAYERS IN EACH SEGMENT FORMAT ( NI2)      119
C          120
C      CARDS 7 THETAD      ANGLE OF EACH SEGMENT, IN DEGREES, IF ALL SEGMENTS      121
C          ARE EQUAL INPUT ONLY THE FIRST. FORMAT ( N I2)      122
C          THE SUM OF THE N ANGLES MUST EQUAL 90      123
C          124
C      CARDS 8 ON TWO CARDS (10F8.5)      125
C          EMISIP(I) EMISIVITY OF EACH PAYLOAD SEGMENT (MAXIMUM 10)      126
C          TPAY(I)    TEMPERATURE OF EACH PAYLOAD SEGMENT (MAXIMUM 10)      127
C          128
C      CARDS 9 EMIST EMISSIVITY OF EACH SURFACE, RADIATION (8F10.5)      129
C          130
C      CARD 10 NHIK NO. OF HIGH CONDUCTIVITY LAYERS (30I2)      131
C          NUMHIK LAYER NUMBERS WHICH ARE HI COND.      132
C          133
C      CARDS 11 NNODS IF INITIAL TEMPS READ FROM CARDS - NO. OF NODES      134
C          T(I) INITIAL TEMPERATURES, DEG. R (I8,9F8.1/10F8.1)      135
C          136
C          READ(NIN,1001) NSEG,NPAY,NSPL,DELS,TWALL,TSURF,TSPACE,EMISS,
C          1 SPACEE,RP,TCARDS,X,Y,H,CON1,CON2,IEXECN,NPRINT,NDAMP,
C          2 DELDMP,CINCON
C          DPTH=DELS*FLOAT(NSPL)
C          THIKN= DPTH
C          HH=H .
C          NSEG=NSEG
C          NPAY= NPAY
C          TNODE=J.0
C          READ(5,1003) NTAB, (AKVST(I),I=1,NTAB)
C          HIKCON=AKVST(NTAB)
C          IF(NSEG.GT.30) NSEG=30
C          IFMT1(2)= NBCD(NSEG)
C          IFMT1(4)= NBCD(NSEG)
C          READ(NIN,IFMT1) (NL(I),I=1,NSEG),(THETAD(I),I=1,NSEG),EMISP,TPAY
C          READ(NIN,1004) (EMIST(I),I=1,NSEG)
C          READ(NIN,1002) NHIK,(NUMHIK(I),I=1,NHIK)
C          NSURF= NSEG + NPAY + 1
C          NSURFS=NSURF
C          NOFA= (NSURF*(NSURF+1)/2)+2
C          J=NSEG+1
C          MAXNL=0
C          DO 201 I=1,NSEG
C          201 IF(NL(I) .GT. MAXNL) MAXNL=NL(I)
C          DO 200 I=J,NSURF
C          M=I-J+1
C          200 EMIST(I)= EMISP(M)
C          EMIST(NSURF)=SPACEE
C          DO 2 I=1,50
C          2 ITEST(I)= I
C          IF(NHIK .LE. 0) GO TO 4
C          DO 3 I=1,NHIK
C          M= NUMHIK(I)
C          3 ITEST(M)= -ITEST(M)
C          4 CONTINUE
C          IFMTH(4)=ISPS
C          IF(IEXECN .EQ. ISL .OR. IEXECN .EQ. IWBK .OR. IEXECN .EQ. IBACK
C          1 .OR. IEXECN .EQ. IVARB) IFMTH(4)=ILPS
C          IF(THETAD(2) .GT. 0.) GO TO 5
C          DO 6 I=2,NSEG
C          6 THETAD(I)= THETAD(1)

```

```

5 BTA(1)= 0. 178
DO 9 I=2,NSEG 179
9 BTA(I)= BTA(I-1) + THETAD(I-1) 180
BTA(NSEG+1)=90.0 181
WRITE(LCK2,IFMTH) 182
WRITE(LCK2,2001) ID 183
NSEGP1= NSEG+1 184
7001 NNL= 1 185
7002 NREAL= NSEG+2 186
7003 NREALN= NREAL+NSEGP1 187
7004 NARCLN=NREALN+NSURF+1 188
7005 NTHTETA= NARCLN+NSEGP1 189
7006 NTEST=NTHTETA+NSEGP1 190
7007 NKHIC= NTEST+51 191
7008 NEMISS= NKHIC+NTAB+1 192
7009 NAFA=NEMISS+NSURF+1 193
7010 NSNT=NAFA+NOFA+1 194
C 195
C GENERATE NODE DATA 196
C NODE NO. FOR SPACE IS NNODES 197
C NODE NO. FOR FIRST PAYLOAD NODE IS (NNODES-NPAY) 198
C NODE NO. FOR TANKWALL IS (NNODES-NPAY-1) 199
C 200
C SHIELD NODES 201
C 202
C WRITE(LCK2,2032) 203
101 NNODES=0 204
C 205
C GENERATE INTERIOR NODES 206
C 207
C DO 10 I=1,NSEG 208
10 NNODES= NNODES + NL(I) 209
NINSN=NNODES 210
C 211
C ADD NO. OF SURFACE NODES TO NNODES, SURF NODES ONLY ALONG TANKWALL 212
C 213
C NNODES=NNODES+NSEG 214
TEMP= TNODE 215
WRITE(LCK2,2003)M1 ,NNODES,M1 ,TEMP,ONE,ONE,ONE,ONEM 216
C 217
C TANKWALL NODE 218
C 219
C NNODES= -NNODES-1 220
TEMP= TWALL 221
WRITE(LCK2,2004) NNODES,TEMP,ONE 222
C 223
C PAYLOAD NODES (BOUNDARY NODES) 224
C 225
C DO 105 I=1,NPAY 226
NNODES=NNODES-1 227
TEMP=TPAY(I) 228
WRITE(LCK2,2004) NNODES,TEMP,ONE 229
105 CONTINUE 230
C 231
C NODE FOR SPACE (BOUNDARY NODE) 232
C 233
C NNODES = NNODES-1 234
TEMP= TSPACE 235
WRITE(LCK2,2004) NNODES,TEMP,ONE 236
104 WRITE(LCK2,2007) 237
NNODES= IABS(NNODES) 238
IF(TCARDS .EQ. 0.) GO TO 115 239

```

```

      READ(NIN,1005) NNSPCH,(T(I),I=1,NNSPCH)          240
      GO TO 110                                         241
115  CONTINUE                                         242
      N=0                                               243
      IF(TSJRF) 207,207,208                           244
C
C  CONSTANT INITIAL TEMPS                         245
C
207  TS=ABS(TSURF)                                248
      DELT=0.0                                         249
      GO TO 205                                         250
C
C  DISTRIBUTE TEMPS BETWEEN TWALL AND TSURF       251
C
208  DELT=(TSURF-TWALL)/FLOAT(MAXNL)              254
      TS=TWALL                                         255
205  DO210 I=1,NSEG                                256
      NLAY=NL(I)+1                                    257
      N=N+1                                           258
      T(N)=TS                                         259
      DO211 J=2,NLAY                                 260
      N=N+1                                           261
      T(N)=T(N-1) +DELT                            262
211  CONTINUE                                         263
210  CONTINUE                                         264
      DO 212 I=1,N                                     265
212  T(I)=T(I)-TABS                               266
110  T(NNODES)=TSPACE -TABS                      267
      M=NNODES-NPAY-1                             268
      DO 213 I=1,NPAY                            269
      J=M+I                                         270
213  T(J)=TPAY(I)-TABS                          271
      T(M)=TWALL-TABS                           272
      WRITE(LUT5) (T(I),I=1,NNODES)                273
C
C  COMPUTE AREAS FOR LATERAL (HORIZ), AND NORMAL (VERT), CONDUCTORS 274
C  PUT AREAS INTO ARRAYS AREAL, AND AREAN AND OUTPUT IN ARRAY DATA AS 275
C  ARRAY 2 AND ARRAY 3 RESPECTIVELY.                                276
C  ARRAY ARCLN, LENGTHS OF NODES, IS ARRAY 4.                         277
C
80   CONTINUE                                         278
      ASQ=X*X                                         279
      BSQ=Y*Y                                         280
      ASQBSQ= ASQ*BSQ                                281
      ERAD(1)=Y                                       282
      K=0                                             283
      DO 20 I=1,NSEG                                284
      ANG1= BTA(I)                                    285
      ANG2= BTA(I+1)                                286
      THETA(I)= THETAD(I)*0.01745329               287
      M= THETAD(I)                                288
      DLAY=NL(I)                                    289
      DO 81 L=1,M                                  290
      K=K+1                                         291
81   SLAY(K)=DLAY                                292
      ANG2= ANG2*0.01745329                         293
      SINAL= SIN(ANG2)                            294
      COSAL= COS(ANG2)                            295
      SSQ= SINAL**2                                296
      CSQ= COSAL**2                                297
      ERAD(I+1)= SQRT(ASQBSQ / (BSQ*SSQ + ASQ*CSQ) ) 298
      DMLI= DPTH*FLOAT(NL(I))                      299
      R1= ERAD(I)+DMLI                            300
      R2= ERAD(I+1)+DMLI                           301

```

```

RAD= (R1+R2)/2.          304
ARCLN(I)= RAD*THETA(I)  305
SMALLR= R2* SINAL      306
ENDW= SMALLR* PI04      307
AREAL(I)= ENDW * DPTH   308
20 CONTINUE               309
    CALL VIEWF             310
C                                     311
C   GENERATE CONDUCTOR DATA , ALL CONDUCTANCE VALUES WILL BE COMPUTED 312
C   IN VARIABLES 1 (THEREFORE 1.0 WILL BE USED                         313
C   IN THIS ROUTINE FOR C.)                                         314
C                                     315
C   WRITE(LCK2,2005)           316
C   NORMAL CONDUCTORS IN SHIELD                           317
C                                     318
C   NODA=1              319
C   NCOND=1             320
DO 11 I=1,NSEG            321
NLAY=NL(I)                322
NODB=NODA+1                323
WRITE(LCK2,2006)NCOND,NLAY,M1,NODA,M1,NODB,M1,ONE,ONE,ONE,ONE 324
NODA=VDDA+NLAY+1          325
11 NCOND=NCOND+NLAY        326
C                                     327
C   LATERAL CONDUCTORS IN SHIELD                           328
C                                     329
C   NODA=2              330
DO 15 I=2,NSEG            331
NLAY=NL(I)                332
NLM1P2=NL(I-1)+1          333
NODB=NODA+NLM1P2          334
WRITE(LCK2,2006)NCOND,NLAY,M1,NODA,M1,NODB,M1,ONE,ONE,ONE,ONE 335
NODA=NODB                336
15 NCOND=NCOND+NLAY        337
C                                     338
C   CONDUCTORS FROM EDGE OF SHIELD TO TANKWALL             339
C                                     340
C   NODA=0              341
NODB=NNODES-NPAY-1        342
NCOND=NCOND-1             343
144 DO 14 I=1,NSEG         344
NODA=VDDA+1                345
NCOND=VCOND+1              346
WRITE(LCK2,2026) NCOND,NODA,NODB,TEN20 347
14 NODA= NODA+NL(I)        348
C                                     349
C   COMPUTE TABLE OF SURFACE NODE NUMBERS                  350
C                                     351
C   NODA=0              352
DO 16 I=1,NSEG            353
NODA= NODA+NL(I)+1        354
NSNOD(I)= NODA             355
16 CONTINUE               356
J=NSEG+1                  357
JJ=NNODES-NPAY-J          358
DO 162 I=J,NSURF          359
162 NSNOD(I)=JJ+I          360
WRITE(LCK2,2007)             361
C                                     362
C   GENERATE CONSTANTS DATA                            363
C                                     364
WRITE(LCK2,2008) (I,C(I),I=1,20)                 365

```

```

      WRITE(LCK2,2024) (I,C(I),I=21,28)          366
      WRITE(LCK2,2010) (I,C(I),I=29,36)          367
      WRITE(LCK2,2022) (CONNAM(I),CINCON(I),I=1,10) 368
      WRITE(LCK2,2007)                           369
C
C   GENERATE ARRAY DATA BLOCK                 370
C     TO OUTPUT ARRAY CALL SUBROUTINE RITARY(N,A,NO,NF,ZN) 371
C       WHERE      N=ARRAY NUMBER             372
C           A=ARRAY TO BE PUT OUT            373
C           NO= NUMBER OF ELEMENTS IN THE ARRAY 374
C           NF= EITHER 1 OR 2    NF=1 IF ARRAY IS FLOATI 375
C                                         NF=2 IF ARRAY IS INTEGE 376
C           ZN=BCD ARRAY WHICH BECOMES A TITLE FOR 377
C             ARRAY N.                      378
C
C   WRITE(LCK2,2009)                         379
C   CALL RITARY(1,NL,NSEG,2,Z1)              380
C   CALL RITARY(2,AREAL,NSEG,1,Z2)           381
C   CALL RITARY(3,A,NSURF,1,Z3)             382
C   CALL RITARY(4,ARCLN,NSEG,1,Z4)           383
C   CALL RITARY(5,THETAD,NSEG,1,Z5)          384
C   CALL RITARY(6,TEST, 50 ,2,Z6)            385
C   CALL RITARY(7,AKVST,NTAB,1,Z7)           386
C   CALL RITARY(8,EMIST,NSURF,1,Z8)          387
C   CALL RITARY(9,AFA,NOFA,1,Z9)             388
C   CALL RITARY(10,NSNOD,NSURF,2,Z10)        389
C   WRITE(LCK2,2007)                         390
C
C   GENERATE EXECUTION BLOCK                391
C
C   WRITE (LCK2,2012)                      392
C   WRITE(LCK2,2020)                      393
C   WRITE(LCK2,2033) IEXECN               394
C   WRITE(LCK2,2007)                      395
C
C   GENERATE VARIABLES 1 BLOCK            396
C
C   WRITE(LCK2,2015)                      397
C   WRITE(LCK2,2007)                      398
C
C   GENERATE VARIABLES 2 BLOCK            399
C
C   WRITE(LCK2,2014)                      400
C   WRITE(LCK2,2031)                      401
C   WRITE(LCK2,2007)                      402
C
C   GENERATE OUTPUT CALLS                403
C
C   WRITE(LCK2,2016)                      404
C   WRITE(LCK2,2029)                      405
C   WRITE(LCK2,2028)                      406
C   WRITE(LCK2,2025)                      407
C   WRITE(LCK2,2030)                      408
C   WRITE(LCK2,2007)                      409
C
C   WRITE SUPPLIED SUBROUTINES ONTO TAPE LCK2 410
C
C   WRITE(LCK2,2017)                      411
C   DO 60 I=1,NSTMTS                   412
C   READ(LUT3)  ISTMT                  413
C   60 WRITE(LCK2,2018)  ISTMT          414
C   WRITE(LCK2,2019)                      415
C   REWIND 2                            416

```

C		429
C WRITE SWITCH SYSIN1 TO SYSUT6, TO READ CINDA DATA BY CINDA		430
C		431
END FILE LCK2		432
WRITE(LCK2,2021)		433
END FILE LCK2		434
END FILE LCK2		435
END FILE LCK2		436
REWIND LCK2		437
WRITE(NOUT,5000)		438
5000 FORMAT(51H END OF PREPRE PGM. NOW SWITCHTO INPUT FOR PREPRO)		439
WRITE(6,5001) NSTMTS		440
5001 FORMAT(45H NO. OF STATEMENTS IN SUBROUTINES LOADED = I5)		441
CALL EXIT		442
READ(NIN,1000) ID		443
1000 FORMAT(13A6,A2)		444
1001 FORMAT(I4,2I3,7F10.5/6F10.5,A6/2I10,F10.5/I8,9F8.3)		445
1002 FORMAT(30I2)		446
1003 FORMAT(I6,12F6.1/(6X,12F6.1))		447
1004 FORMAT(8F10.5)		448
1005 FORMAT(I8,9F8.1/(10F8.1))		449
2000 FORMAT(20H\$EXECUTE IBJOB, 64X /		450
1 34H\$ID COWGILL PREPRO, 50X/ 6H\$IBJOB ,78X /		451
2 27H\$IEDIT SYSCK1,SCHF2 ,57X / 13H\$IBLDR PREPRO ,71X /		452
2 13H\$IBLDR TAPDEF,71X/ 13H\$IBLDR FVIO. ,71X/		453
3 27H\$ORIGIN ALPHA,SYSLB2 ,57X / 13H\$IBLDR GENLNK ,71X /		454
4 27H\$ORIGIN ALPHA,SYSLB2 ,57X / 13H\$IBLDR PSEUDO ,71X /		455
5 13H\$IBLDR PACK43 , 71X / 13H\$IBLDR ORMIN , 71X /		456
6 27H\$ORIGIN ALPHA,SYSLB2 ,57X /		457
7 13H\$IBLDR CODERD , 71X / 13H\$IBLDR DATARD , 71X /		458
8 27H\$ORIGIN ALPHA,SYSLB2 ,57X / 13H\$IBLDR PRESUB ,71X /		459
9 13H\$IBLDR CINDA4 , 71X / 13H\$IBLDR SEARCH, 71X /		460
A 27H\$ORIGIN ALPHA,SYSLB2 ,57X / 13H\$IBLDR COPYSB, 71X /		461
B 13H\$IBLDR LOCATE , 71X / 13H\$IBLDR FIBLDR , 71X /		462
C 13H\$IBLDR READTP . 71X / 13H\$IBLDR CIN90 , 71X /		463
D 27H\$ORIGIN ALPHA,SYSLB2 ,57X / 13H\$IBLDR INITAL , 71X /		464
E 27H\$ORIGIN ALPHA,SYSLB2 ,57X / 13H\$IBLDR FINAL , 71X /		465
F 27H\$ORIGIN ALPHA,SYSLB2 ,57X /		466
G 13H\$IBLDR SKIP , 71X / 13H\$IBLDR SPLIT , 71X /		467
H 5H\$DATA , 79X / 80X)		468
2001 FORMAT(7X,5HBCD 9,9A6,14X/7X,5HBCD 5,5A6,38X/7X,3HEND,70X)		469
2003 FORMAT(470
1 7X,4HGEN ,I1,1H,,I4,1H,,I1,1H,,F7.2,1H,,F3.1,1H,,F3.1,		471
2 1H,,F4.1,36X)		472
2004 FORMAT(11X,15,1H,,F6.1,1H,,F4.1,52X)		473
2005 FORMAT(7X,19HBCD 3CONDUCTOR DATA ,54X)		474
2006 FORMAT(7X,4HGEN ,7(I4,1H,),3(F3.1,1H,),F3.1,19X)		475
2007 FORMAT(7X,3HEND,70X)		476
2008 FORMAT(7X,19HBCD 3CONSTANTS DATA,54X /		477
1 (11X,4(I3,1H,,I5,1H,,),I3,1H,,I5,20X))		478
2009 FORMAT(7X,15HBCD 3ARRAY DATA,58X)		479
2010 FORMAT((11X,3(I2,1H,,F13.5,1H,,),I2,1H,,F13.5,2X))		480
2012 FORMAT(7X,14HBCD 3EXECUTION,59X/23HF DIMENSION X(3000),57X /		481
1 15HF NDIM=3000,65X / 12HF NTH=0,68X)		482
2014 FORMAT(7X,16HBCD 3VARIABLES 2,57X)		483
2015 FORMAT(7X,16HBCD 3VARIABLES 1, 57X /15HF CALL GETG,65X)		484
2016 FORMAT(7X,17HBCD 3OUTPUT CALLS,56X)		485
2017 FORMAT(7X,16HBCD 3SUBROUTINES ,57X)		486
2018 FORMAT(13A6,A2)		487
2019 FORMAT(7X,16HBCD 3END OF DATA ,57X)		488
2020 FORMAT(11HF NN=10,69X/22HF IF(NN.GT.0)GOTO3,58X /		489
1 11X,24HLAGRAN(RTEST,STEST,A7,7) ,45X/		490

2	11X,22HIRRAD(A3,A8,A9,STEST)	,47X	/	491
2	14HF	3 CONTINUE,66X /		492
2	16HF	CALL TDIST,64X)		493
2021	FORMAT(6H\$IBSYS,74X/21H\$REWIND	SYSUT6,59X/28H\$SWITCH	SYSIN1,SYSLB3,52X/	494
1	21H\$REWIND	SYSUT6,59X/28H\$SWITCH	SYSIN1,SYSLB3,52X/	495
2	28H\$SWITCH	SYSIN1,SYSCCK2,52X)		496
2022	FORMAT(11X,A6,1H,,I4,3(1H,,A6,1H,,F9.6),7X /			497
1	11X,A6,1H,,F9.6,3(1H,,A6,1H,,F9.4),2X /			498
2	11X,A5,1H,,F9.6,1H,,A6,1H,,F9.6,36X)			499
2023	FORMAT(12X,3HEND,65X)			500
2024	FORMAT((11X,3(I2,1H,,1PE13.6,1H,,),I2,1H,,1PE13.6,2X))			501
2025	FORMAT(26HF WRITE(6,1000) LOOPCT,54X /			502
1	28HF1000 FORMAT(9HL LOOPCT= I6),52X)			503
2026	FORMAT(11X,3(I5,1H,,),3X,A6,42X)			504
2027	FORMAT(11X,3(I5,1H,,),E16.8,35X)			505
2028	FORMAT(11X,6HPRNTMP,63X)			506
2029	FORMAT(13HF NN=K(4),67X/			507
1	18HF DO 10 I=1,NN, 62X /			508
2	22HF 10 T(I)=T(I)+460.0 ,58X)			509
2030	FORMAT(18HF DO 11 I=1,NN,62X/			510
2	22HF 11 T(I)=T(I)-460.0 ,58X)			511
2031	FORMAT(17HF CALL ENDOUT,63X)			512
2032	FORMAT(7X,14HBCD 3NODE DATA,59X)			513
2033	FORMAT(11X,A6,63X)			514
	END			515

\$IBFTC VIEWFC

	SUBROUTINE VIEWF	1
C	RADIATION VIEW FACTOR BETWEEN FLAT SURFACED PAYLOAD AND SPHEROIDAL	2
C	TANK WITH VARYING MLI THICKNESS.	3
C	INPUT REQUIRED	4
C	SLAY - NO. OF NODES IN EACH 1 DEGREE SEGMENT	5
C	RP - PAYLOAD RADIUS	6
C	X AND Y - MAJOR AND MINOR RADII OF TANK (WITHOUT COVERING)	7
C	NSEG - NO. OF SEGMENTS ON TANK	8
C	NPAY - NO. OF RINGS ON PAYLOAD	9
C	NSURF- TOTAL NO. OF SURFACES IN RADIATION ENCLOSURE	10
C	H - TANK TO PAYLOAD SPACING	11
COMMON /RADIO/ NSEG,NPAY,NSURF,X,Y,H,RP,THIKN,PI,SLAY,THETA,A,AFA	12	
COMMON /TAPE/ NIN,NOUT,LCK2	13	
DIMENSION SLAY(90),A(41),AFA(1681),THETA(30)	14	
DIMENSION SAREA(90),DAREA(90),SEGA(100),DF(600),F(600),R(10)	15	
DIMENSION SAF(90,100),AF(41,41),RVF(41,41)	16	
DATA W1,W2,W3,W4,W5,W6,EY1,EY2 /6H A,6H R,6H DAREA,	17	
1 6H SEGA,6H RFV,6H AF,6H(I) ,6H(I,J) /	18	
TOP1=2.*PI	19	
ONED= PI/180.	20	
HALFD=ONED/2.	21	
RPSQ=RP*RP	22	
N=10.*RP	23	
PSI=-HALFD	24	
DO 28 K=1,90	25	
PSI=PSI+ONED	26	
10 DMLI= SLAY(K)*THIKN	27	
AX=X+DMLI	28	
BX=Y+DMLI	29	
AXSQ=AX*AX	30	

```

BXSQ=BX*BX 31
SPSI=SIN(PSI) 32
CPSI=COS(PSI) 33
SSQ=SPSI*SPSI 34
CSQ=CPSI*CPSI 35
AXBX=AX*BX 36
R1= AXBX*SQRT(1./(BXSQ*SSQ+AXSQ*CSQ)) 37
Y1=R1*SPSI 38
Z1=R1*CPSI 39
DH=BX-Z1 40
XM1=(AXSQ*Z1)/(BXSQ*Y1) 41
WSQ=(AXSQ-BXSQ)/BXSQ/BXSQ 42
W=SQRT(WSQ) 43
HOW=0.5/W 44
SRQB=SQRT(1.+WSQ*BXSQ) 45
RJ=BX/2.*SRQB 46
S= HOW*ALOG(BX*W+SRQB) 47
UPLIM=RJ+S 48
PSIX=PSI+HALFD 49
SPX=SIN(PSIX) 50
CPX=COS(PSIX) 51
SPXSQ=SPX*SPX 52
CPXSQ=CPX*CPX 53
R1X= AXBX*SQRT(1./(BXSQ*SPXSQ+AXSQ*CPXSQ)) 54
Z1X=R1X*CPX 55
SRQZX=SQRT(WSQ*Z1X**2+1.) 56
T=Z1X/2.*SRQZX 57
U= HOW*ALOG(Z1X*W+SRQZX) 58
BOTLIM= T+U 59
SAREA(K)=TOPI*AX*(UPLIM-BOTLIM) 60
IF(K.EQ.1) GO TO 12 61
DAREA(K)=SAREA(K)-SAREA(K-1) 62
GO TO 14 63
12 DAREA(K)=SAREA(K) 64
14 DO 28 I=1,N 65
RING=I 66
RHO=.1*(RING-.5) 67
SIXRNG=6.*RING 68
SEGA(I)=PI*{(.1*RING)**2-(.1*(RING-1.))**2}/SIXRNG 69
NSGT=5*I 70
GAMA=0. 71
DO 24 J=1,NSGT 72
IF(J.EQ.1) GO TO 16 73
GAMA=GAMA+(TOPI/SIXRNG) 74
16 X2=RHO*COS(GAMA) 75
Y2=RHO*SIN(GAMA) 76
XA= X2 77
YB= Y2-Y1 78
ZC= H-DMLI+DH 79
RV=SQRT(XA**2+YB**2+ZC**2) 80
SM= SQRT(1.+XM1**2) 81
COSP1= (YB+XM1*ZC)/(RV*SM) 82
COSP2= ZC/RV 83
IF(COSP1.LE.0.) GO TO 18 84
DF(J)=(COSP1*COSP2*SEGA(I))/(PI*RV*RV) 85
GO TO 20 86
18 DF(J)=0. 87
20 IF(J.EQ.1) GO TO 22 88
F(J)=DF(J)+F(J-1) 89
GO TO 24 90
22 F(J)=DF(J) 91
24 CONTINUE 92
SAF(K,I)=DAREA(K)*F(NSGT) 93

```

```

28 CONTINJE          94
  XNPAY=NPAY          95
  DO 30 II=1,NPAY    96
  XI=II               97
  RR=SQRT((RPSQ*XI)/XNPAY) 98
  NDELR=10.*RR        99
  XNDELR=NDELR       100
  R(II)=.1*XNDELR    101
  JJ=II+NSEG         102
  IF(II.EQ.1) GO TO 29 103
  A(JJ)= PI*(R(II)**2-R(II-1)**2) 104
  GO TO 30            105
29 A(JJ)=PI*R(II)**2 106
30 CONTINJE          107
  DO 304 KK=1,NSEG   108
  IF(KK.EQ.1) GO TO 301 109
  NDEG1=NDEG2+1      110
  NDEG=THTETA(KK)    111
  NDEG2=NDEG1+NDEG-1 112
  GO TO 302           113
301 NDEG1=1          114
  NDEG2=THETA(KK)    115
302 ASUM=0.           116
  DO 303 K=NDEG1,NDEG2 117
  ASUM=ASUM+DAREA(K) 118
303 CONTINUE          119
  A(KK)=ASUM          120
304 CONTINUE          121
  A(NSURF)= 122.211   122
  DO 40 KK=1,NSEG    123
  IF(KK.EQ.1) GO TO 32 124
  NDEG1=NDEG2+1      125
  NDEG=THTETA(KK)    126
  NDEG2=NDEG1+NDEG-1 127
  GO TO 34            128
32 NDEG1=1          129
  NDEG2=THETA(KK)    130
34 DO 40 II=1,NPAY   131
  IF(II.EQ.1) GO TO 36 132
  NDR1=NDR2+1         133
  NDR2=10.*R(II)      134
  GO TO 37            135
36 NDR1=1           136
  NDR2=10.*R(II)      137
37 SUM=0.             138
  DO 38 K=NDEG1,NDEG2 139
  DO 38 I=NDR1,NDR2   140
  SUM=SUM+SAF(K,I)    141
38 CONTINUE          142
  JJ=II+NSEG          143
  AF(KK,JJ)=SUM       144
40 CONTINUE          145
  DO 42 I=1,NSEG     146
  DO 42 J=I,NSEG     147
42 AF(I,J)=0.         148
  NS1=NSEG+1          149
  NS2=NSURF-1         150
  DO 44 I=NS1,NS2     151
  DO 44 J=I,NS2     152
44 AF(I,J)=0.         153
  AF(NSURF,NSURF)=0. 154
  DO 48 I=1,NSEG     155
  SUM=0               156

```

DO 46 K=NS1,NS2	157
46 SUM=SUM+AF(I,K)	158
48 AF(I,NSURF)=A(I)-SUM	159
DO 52 I=NS1,NS2	160
SUM=0	161
DO 50 K=1,NSEG	162
50 SUM=SUM+AF(K,I)	163
52 AF(I,NSURF)=A(I)-SUM	164
DO 60 KK=1,NSEG	165
DO 60 JJ=NS1,NSURF	166
60 RVF(KK,JJ)=AF(KK,JJ)/A(KK)	167
AFA(1)=0.0	168
AFA(2)=0.0	169
I=2	170
DO 100 KK=1,NSURF	171
DO 100 JJ=KK,NSURF	172
I= I+1	173
100 AFA(I)= AF(KK,JJ)	174
Z1=W1	175
Z2=EY1	176
WRITE(NOUT,1001) Z1,Z2,(A(I),I=1,NSURF)	177
Z1=W2	178
WRITE(NOUT,1001) Z1,Z2,(R(I),I=1,NPAY)	179
Z1=W3	180
WRITE(NOUT,1001) Z1,Z2,(DAREA(I),I=1,90)	181
Z1=W4	182
WRITE(NOUT,1001) Z1,Z2,(SEGA(I),I=1,N)	183
Z1=W5	184
Z2=EY2	185
WRITE(NOUT,1001) Z1,Z2	186
DO 200 KK=1,NSEG	187
WRITE(NOUT,1002) (RVF(KK,JJ),JJ=NS1,NSURF)	188
200 CONTINUE	189
Z1=W6	190
WRITE(NOUT,1001) Z1,Z2	191
DO 1100 KK=1,NSURF	192
WRITE(NOUT,1002) (AF(KK,JJ),JJ=KK,NSURF)	193
1100 CONTINUE	194
RETURN	195
1001 FORMAT(1HK,2A6/(1X,1P10E13.5))	196
1002 FORMAT(1X,1P10E13.5)	197
END	198

\$IBFTC RAYOUT

SUBROUTINE RITARY(NA,A,N,J,HEAD)	1
DIMENSION A(1), IFMT1(5), IFMT2(7)	2
DIMENSION HEAD(9)	3
COMMON/BCD/ NBCD(60)	4
COMMON /TAPE/ NIN,NDUT,LCK2	5
DATA IFMT1(1) /30H(12X,4 ,1H,), 4X) / X) /	6
DATA IFMT2(1) /42H(12X,	7
DATA IFLOT1 , IFLOT2 , IFLOT3	8
1 / 6H(F12.7 , 6HF12.7, , 6H,1H,), /	9
DATA IFIX1 , IFIX2 , IBLANK	10
1 / 6H (I12 , 6H I12, , 6H /	11
DATA IE1 • IE2	12

```

1 / 6H(E12.5   .   6HE12.5,   /
NSEG= N
JJ= J
IFMT2(3)= IBLANK
IFMT2(4)= IBLANK
ITEM2= IFLOT3
GO TO {10,11,12},JJ
12 IFMT1(2)=IE1
IFMT1(4)=IE2
IFMT2(5)=IE2
ITEM1=IE1
GO TO 21
10 IFMT1(2)= IFLOT1
IFMT1(4)= IFLOT2
IFMT2(5)= IFLOT2
ITEM1= IFLOT1
GO TO 21
11 IFMT1(2)= IFIX1
IFMT1(4)= IFIX2
IFMT2(5)= IFIX2
ITEM1= IFIX1
21 N1= 1
N2= 5
WRITE(LCK2,2011) NA,(HEAD(I),I=1,9)
31 IF (N2 .GE. NSEG) GO TO 40
WRITE (LCK2,IFMT1) (A(I),I=N1,N2)
N1= N1+5
N2= N2+5
GO TO 31
40 NN= NSEG-N1
N2= NSEG
IF(NN .LE. 0) GO TO 39
IFMT2(3)= ITEM1
IFMT2(4)= ITEM2
IFMT2(2)= NBCD(NN)
NBL= 56-13*NN
42 IFMT2(6)= NBCD(NBL)
WRITE(LCK2,IFMT2) (A(I),I=N1,N2)
WRITE (LCK2,2013)
RETURN
39 NN=1
IFMT2(2)=NBCD(NN)
NBL=56
GO TO 42
2011 FORMAT(11X,I2,3H $,9A6,10X)
2013 FORMAT(12X,3HEND,65X)
END

```

\$IBFTC COMDAT

BLOCK DATA										1		
COMMON /BCD/ NBCD(60)										2		
DATA NBCD(1) /360H										3		
1	9	10	11	12	13	14	15	16	17	18	19	4
2	20	21	22	23	24	25	26	27	28	29	30	5
3	31	32	33	34	35	36	37	38	39	40	41	6
4	42	43	44	45	45	47	48	49	50	51	52	7
5	53	54	55	56	57	58	59	60				8
END										9		

\$IBFTC CNDCTR

```
SUBROUTINE GETG          1
COMMON /KONST/ NSEG,NPAY,NSURF,NNODES,MAXNL,NPRINT,NDAMP,NNL,   2
1 NAREAL,NAREAN,NARCLN,NTHETA,NITEST,NKHIC,NEMISS,NAFA,NSNT,   3
2 NEXTRA(3),          4
3 SIGMA,DPTH,DELS,EMISS,CON1,CON2,DELDMP,X,TABS,HIKCON,NPSWCH,RAD,H 5
COMMON /COND/ G(1)      6
COMMON /TEMP/ T(1)      7
COMMON /SOURCE/ Q(1)     8
COMMON /ARRAY/ A(1)     9
COMMON /FIXCON/ KA(1)   10
COMMON/QCOM/ QTS(30),QNORM(30) 11
DIMENSION SAREA(41),EMISIV(41),TQ(41),NTQ(1),NARY(1) 12
EQUIVALENCE (A,NARY), (TQ,NTQ) 13
EQUIVALENCE (NLOOP,KA(5)),(DAMPA,KA(9)),(LOOPCT,KA(20)) 14
EQUIVALENCE (ARLXCC,KA(30)) 15
DATA NTIME /1/          16
NPSWCH=0                17
IF(LOOPCT.GE.NLOOP) CALL PCHT(1) 18
IF(NPSWCH .GT. 0) GO TO 9998 19
IF(ARLXCC .LT. .01) DAMPA=DAMPA+DELDMP 20
IF(DAMPA .GT. 1.0) DAMPA=1.0 21
IF(MOD(LOOPCT,100) .NE. 0) GO TO 32 22
CALL TIMLFT(TLEFT)        23
TLEFTM=TLEFT/3600.        24
WRITE(6,9999) TLEFTM,LOOPCT 25
IF(TLEFT .LT. 14400.0) CALL PCHT(2) 26
IF(NPSWCH .GT. 0) GO TO 9998 27
32 CONTINUE               28
IF(MOD(LOOPCT,NPRINT) .NE. 0) GO TO 33 29
35 NSP1=NSURF+1           30
CALL ENDOUT               31
WRITE(6,1001) LOOPCT,DAMPA,(TQ(I),I=1,NSP1) 32
33 CONTINUE               33
NRAD=RAD                 34
C
C GET G FOR ALL NORMAL (VERTICAL) CONNECTORS 35
C
AKPART= DELS*SIGMA/((2./EMISS)-1.) 36
NODA= 0                      37
NCOND= 0                      38
N1= 1                        39
DO 11 I=1,NSEG               40
M=NNL+I                      41
NLAY= NARY(M)                42
MA= NAREAN+I                 43
ADD=A(MA)/DPTH /8.            44
N2=N1+NLAY-1                 45
30 DO 12 J=N1,N2               46
NODA= NODA+1                 47
NODB= NODA+1                 48
T1= T(NODA) +TABS             49
T2= T(NODB) +TABS             50
TPART= (T1+T2)*(T1*T1+T2*T2) 51
AK= AKPART*TPART              52
G(J)=ADD*AK                  53
G(J)=ADD*AK                  54
12 CONTINUE                   55
NT2=NODA                      56
41 N3=NODB-NLAY               57
N4=N3+1                      58
G(N1)=G(N1)*2.                59
QNORM(I)=G(N1)*(T(N4)-T(N3)) 60
                                         61
```

```

43 CONTINUE          62
    N1= N2+1          63
40 TSURF=T(NT2)      64
11 NODA= NODA+1      65
C                                         66
C COMPUTE G FOR LATERAL CONNECTORS        67
C                                         68
    NODA= 1            69
    NCOND= N2          70
    DO 15 I=2,NSEG     71
    M=NNL+I           72
    NLAY= NARY(M)      73
    NLM1P2=NARY(M-1)+1 74
    L=NARCLN+I         75
    EL1=A(L-1)/2.      76
    EL2=A(L)/2.        77
    LL=NAREAL+I-1      78
    AREA=A(LL)         79
    DO 13 J=1,NLAY     80
    NODA= NODA+1       81
    NODB= NODA+NLM1P2   82
    NCOND= NCOND+1     83
    T1= T(NODA) +TABS   84
    T2= T(NODB) +TABS   85
    MM=NITEST+J         86
    ITEST=NARY(MM)       87
    IF(ITEST)20,19,19     88
20  MMM=NKHIC          89
    IF(T1 .GT. 240.) GO TO 18      90
    CALL LAGRAN(T1,AK1,A(MMM),7)    91
17  IF(T2 .GT. 240.) GO TO 16      92
    CALL LAGRAN(T2,AK2,A(MMM),7)    93
    GO TO 21             94
18  AK1=HIKCON          95
    GO TO 17             96
16  AK2=HIKCON          97
    GO TO 21             98
19  AK1=CON1*T1 + CON2      99
    AK2=CON1*T2 + CON2
21  DEN= EL1/AK1 + EL2/AK2     100
    G(NCOND)= AREA/DEN        101
13  CONTINUE            102
15  NODA=NODA+1          103
C                                         104
C COMPUTE SOURCE TERMS FOR NET Q, RADIOSITY, USING SUBR. IRRADI FOR 105
C INTERCHANGE BETWEEN FACE OF SHIELD AND PAYLOAD                 106
C                                         107
C                                         108
    GO TO (600,601),NTIME          109
600 NTIME=2            110
    J=NSURF+1          111
    M=NAREAN-1          112
    K=NEMISS-1          113
    DO 602 I=1,J         114
    MM=M+I             115
    KK=K+I             116
    SAREA(I)=A(MM)       117
    EMISIV(I)=A(KK)       118
602 CONTINUE            119
    NARY(NAFA+1)=NSURF      120
    A(NAFA+2)=SIGMA        121
    WRITE(6,1000) (SAREA(I),I=1,J) 122
    WRITE(6,1000) (EMISIV(I),I=1,J) 123

```

601	CONTINUE	124
	DO 500 I=1,NSURF	125
	K=NSNT+I	126
	J=NARY(K)	127
500	TQ(I+1)=T(J)	128
	NTQ(1)=NSURF	129
	CALL IRRADI(SAREA,EMISIV,A(NAFA),TQ)	130
	DO 505 I=1,NSEG	131
	K=NSNT+I	132
	J=NARY(K)	133
	Q(J)=Q(J)+TQ(I+1) /8.	134
	QTS(I)=Q(J)	135
505	CONTINUE	136
9998	RETURN	137
1000	FORMAT(1X,10G13.5)	138
1001	FORMAT(10HL LOOPCT= I6, 5X,6HDAMPA= F6.4, 1 /22H NET Q FROM RADIOSITY/(1X,10G13.5))	139
9999	FORMAT(12H TIME LEFT= F15.2, 10H LOOPCT= I8) END	140 141 142

\$IBFTC OUTEND

	SUBROUTINE ENDOUT	1
	COMMON/TITLE/ HEAD(20)	2
	COMMON /KONST/ K(1)	3
	COMMON/FIXCON/ X(27),L,NP	4
	COMMON/QCOM/ QTS(30),QNORM(30)	5
	DIMENSION QTS8(30),QN8(30)	6
	NSEG=K(1)	7
	STS=0.	8
	SNO=0.	9
	CALL PICTR	10
DO 10	I=1,NSEG	11
	QTS8(I)= QTS(I)*8.	12
	QN8(I) = QNORM(I)*8.	13
	STS=STS+QTS(I)	14
10	SNO=SNO+QNORM(I)	15
	STS8=STS*8.	16
	SNO8=SNO*8.	17
	WRITE(6,2000) (HEAD(I),I=1,20),(I,QTS(I),QNORM(I), 1 QTS8(I),QN8(I),I=1,NSEG)	18
	WRITE(6,2001) STS,SNO,STS8,SNO8	19
	N=K(31)	20
	L=0	21
	NP=0	22
	IF(N .EQ. 0) GO TO 4	23
	GO TO (1,2),N	24
1	WRITE(6,2003)	25
	GO TO 3	26
2	WRITE(6,2002)	27
3	WRITE(6,2004)	28
4	RETURN	29
2000	FORMAT(1H1,10X,20A6/9HL NO. SEG,8X,3HQTS,11X,5HQNORM, 1 24X,5HQTS*8,9X,7HQNORM*8 //	30
	2 (18,4X,2F14.8,15X,2F14.8))	31
2001	FORMAT(12HLSUMMATION ,2G14.5,15X,2G14.5)	32
2002	FORMAT(71HLNOTE....THIS CASE STOPPED FOR TIME EXCEEDED, IT HAS NO 1T YET CONVERGED.)	33
2003	FORMAT(52HL....THIS CASE STOPPED FOR ITERATION COUNT EXCEEDED.)	34
2004	FORMAT(53HKCARDS WERE PUNCHED TO RESTART FROM THIS POINT.) END	35
		36
		37
		38
		39

\$IBFTC DISTRT

```
SUBROUTINE TDIST
COMMON /KONST/ K(1)
COMMON /TEMP/ T(1)
LUT5=11
REWIND LUT5
NNODES=K(4)
12 READ (LUT5) (T(I),I=1,NNODES)
RETURN
END
```

1
2
3
4
5
6
7
8
9

\$IBFTC GRAFIC

```
SUBROUTINE PICTR
COMMON/TITLE/ HEAD(20)
COMMON /TEMP/ T(1)
COMMON /ARRAY/ IA(1)
COMMON /KONST/ NSEG,NPAY,NSURF,NNODES,MAXNL,NPRINT,NDAMP,NNL,
1 NAREAL,NAREAN,NARCLN,NTHETA,NITEST,NKHIC,NEMISS,NAFA,NSNT,
2 NEXTRA(3),
3 SIGMA,DPTH,DELS,EMISS,CON1,CON2,DELDMP,X,TABS,HIKCON,PSWTCH,RAD,H
DIMENSION NODNO(15),TOUT(15), LINE(30), NBCD(50), IFMT(13)
DIMENSION NRENDN(15), NRENDT(15), IFMT1(96), A(1)
EQUIVALENCE (IA,A)
DATA ILINE,IBLANK /6H*****, 6H           /
DATA ITARG /6H$$$$$$/
DATA NBCD(1)/ 300H   1   2   3   4   5   6   7   8   14
1   9   10   11   12   13   14   15   16   17   18   19   15
2   20   21   22   23   24   25   26   27   28   29   30   16
3   31   32   33   34   35   36   37   38   39   40   41   17
4   42   43   44   45   46   47   48   49   50   /   18
DATA IFMT(1)/ 78H(2HP 8X,A1,30A4/2HP A6,A2,A1,          (I6,1X,A1)/2
1HP A6,A2,A1,          (F7.2,A1))   /
DATA IFMT1(1)/576H(1H1,5X,20A6/8X,10(1H*),          (8H*****),2H**,
110X,17(1H*)/8X,1H*,9X,          (8H      ),2H *,10X,1H*,15X,1H*/8X
2,18H* PAYLOAD NODES ,          (8H      ),2H *,10X,7H* SPACE,9X,
31H* /8X,10H* NODE NOS,          18 ,2H *,10X,10H* NODE NO.,I5,2H */2
48X,1H*,9X,          (8H      ),2H *,10X,1H*,15X,1H*/8X,10H* TEMPS=
5 ,          F8.2 ,2H *,10X,7H* TEMP=,F8.2,2H */8X,10H* EMISIV= ,
6          F8.4 ,2H *,10X,8H* EMISIV,F7.4,2H */8X,10(1H*),          (8H***
7****),2H**,10X,17(1H*)/14HKANGLE OF EACH/14H SEGMENT(DEG.)/10X,
8          F8.1/14HKEMISIVITY OF /14H EACH SEGMENT /10X,          F8.4)
9 /
DATA ISU1,ISU2,ITW1,ITW2
1 / 6HSURFAC ,6HE      , 6HTANKWA ,6HLL      /
DO 5 I=1,NNODES
```

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33

```

5 T(I)=T(I)+TABS          34
MAXL= MAXNL+1            35
NSPACE=NNODES            36
NWALL=NSPACE-NPAY-1      37
NCINIT=0                  38
NS1= 1                    39
NS2= NSEG                 40
IF(NSEG .GT. 15) NS2=15   41
8 NTH1 = NTHETA+NS1       42
NTH2 = NTHETA+NS2       43
NP1=NSPACE-NPAY          44
NP2=NSPACE-1              45
NET1=NEMISS+NS1          46
NET2=NEMISS+NS2          47
NEP1=NET1+NSEG           48
NEP2=NEP1+NPAY-1         49
NESPAC=NEMISS+NSEG+NPAY+1 50
IFMT1( 5)= NBCD(NPAY)     51
IFMT1(13)= NBCD(NPAY)    52
IFMT1(24)= NBCD(NPAY-1)   53
IFMT1(35)= NBCD(NPAY)    54
IFMT1(44)= NBCD(NPAY)    55
IFMT1(54)= NBCD(NPAY)    56
IFMT1(64)= NBCD(NPAY)    57
IFMT1(73)= NBCD(NPAY)    58
IFMT1(86)= NBCD(NSEG)    59
IFMT1(95)= NBCD(NSEG)    60
WRITE(6,IFMT1)HEAD,(J,J=NP1,NP2),NSPACE,(T(I),I=NP1,NP2),T(NSPACE) 61
1 , (A(I),I=NEP1,NEP2), A(NESPAC), (A(I),I=NTH1,NTH2),                62
2 (A(I),I=NET1,NET2)        63
  WRITE(6,2004) H             64
  WRITE(6,2003)               65
  DO 10 I=1,MAXL             66
  M=MAXL-I+1                 67
  IM=M-1                     68
9  DO 11 L=1,15              69
  LINE(L)= IBLANK            70
  LINE(L+15)= IBLANK         71
  NODNO(L)= 0                 72
11 TOUT(L)= 0.0              73
  NS1P1= NS1-1                74
  NC=NCINIT                   75
  N= 0                         76
  ISNSW=1                      77
50 IF(M .EQ. 1) GO TO 12      78
  MM1=M-1                      79
52 MM=NITEST+MM1              80
  ITEST=IA(MM)                 81
  IF(ITEST .LT. 0) ISNSW=-1    82
12 DO 20 J=NS1,NS2            83
  N2= 2*(J-NS1P1)              84
  N1= N2-1                      85
  JJ=NNL+J                      86
  JN=J-NS1+1                    87
  NLAY=IA(JJ)+1                 88
  IF(NLAY .LT. M) GO TO 19      89
  N= N+1                        90
C                                     91
C CHECK FOR TOP SURFACE TARGETING 92
C                                     93
26 IF(NLAY .GT. M) GO TO 21      94
C                                     95

```

```

C NLAY =M THIS IS A TOP SURFACE, CHECK TO SEE IF TARGETED      96
C                                                               97
24 JJ=NEMISS+J                                              98
  EMISIV=A(JJ)                                              99
  IF(EMISIV .LT. 0.1) GO TO 21                               100
  LINE(N1)=ITARG                                            101
  LINE(N2)=ITARG                                            102
  GO TO 27                                                 103
C                                                               104
C NL(JJ) M THIS IS AN INTERIOR NODE OR TANKWALL SURFACE. 105
C                                                               106
21 LINE(N1)= ILINE                                         107
  LINE(N2)= ILINE                                         108
27 ISIGN=1                                                 109
  IF(I .LT. MAXL) GO TO 23                               110
  NRENDN(N)=IBLANK                                         111
  NRENDT(N)=IBLANK                                         112
  LEND=IBLANK                                             113
  LLEND=ILINE                                             114
  NAM1=ITW1                                               115
  NAM2=ITW2                                               116
  NAM3=ISU1                                               117
  NAM4=ISU2                                               118
  GO TO 18                                                 119
23 ISIGN=ISNSW                                           120
  LEND=ILINE                                             121
  LLEND=ILINE                                             122
  NAM1=NBCD(IM)                                           123
  NAM2=IBLANK                                             124
  NAM3=IBLANK                                             125
  NAM4=IBLANK                                             126
  NRENDV(N)=ILINE                                         127
  NRENDT(N)=ILINE                                         128
18 NN= NC+M                                              129
  NODNO(JN)= NN*ISIGN                                     130
  TOUT(JN)=T(NN)                                           131
19 NC= NC+NLAY                                           132
20 CONTINUE
  IF(N .GT. 0) GO TO 22
  WRITE(6,2001)
  GO TO 10
22 IFMT( 6)= NBCD(N)
  IFMT(11)= NBCD(N)
  WRITE(6,IFMT)LLEND, ( LINE(L),L=1,30), NAM1,NAM2,LEND,
  1 (NODNO(L),NRENDN(L),L=1,N), NAM3,NAM4,LEND,
  2 (TOUT(L),NRENDT(L),L=1,N)
10 CONTINUE
  DO 31 I=1,3
31 LINE(I)=ILINE
  WRITE(6,2002) (LINE(I),I=1,3), NWALL, T(NWALL), (LINE(I),I=1,3)
  IF(NS2 .GE. NSEG) GO TO 40
  NS1= NS2+1
  NS2= NSEG
  NCINIT=NC
  GO TO 8
40 DO 41 I=1,NNODES
41 T(I)=T(I)-TABS
  RETURN
2000 FORMAT(1H1, 5X,20A6/4IX,17(1H*),10X,17(1H*)/
  1 4IX,1H*,15X,1H*,10X,1H*,15X,1H* /
  2 4IX, 9H* PAYLOAD,7X,1H*,10X,7H* SPACE,9X,1H* /
  3 4IX,10H* NODE NO.,I5,2H *,10X,10H* NODE NO.,I5,2H */

```

4	41X,1H*,15X,1H*,10X,1H*,15X,1H*/	158
5	41X,7H* TEMP=,F8.2,2H *,10X,7H* TEMP=,F8.2,2H */	159
6	41X,1H*,15X,1H*,10X,1H*,15X,1H*/	160
7	41X,17(1H*),10X,17(1H*) /	161
8	14HKANGLE OF EACH / 14H SEGMENT(DEG.) / 10X,15F8.1)	162
2001	FORMAT(2HP /2HP /2HP)	163
2002	FORMAT(2HP /2HP /2HP ,41X,3A6/2HP ,41X,1H*,16X,1H*/	164
1	2HP ,41X,1H*,9H TANKWALL,7X,1H* /	165
2	2HP ,41X,1H*,10H NODE NO.=,I5,2H */	166
3	2HP ,41X,1H*,7H TEMP.= F8.2,2H */	167
4	2HP ,41X,1H*,16X,1H*/2HP ,41X,3A6)	168
2003	FORMAT(7H LAYER /6H NO.)	169
2004	FORMAT(25HKTANK TO PAYLOAD SPACING= F7.4, 4H FT. /)	170
	END	171

\$IBFTC PUNTEM

SUBROUTINE PCHT(N)	1
COMMON /TEMP/ T(1)	2
COMMON /FIXCON/ FC(1)	3
COMMON/KONST/ K(1)	4
C SET NPSWCH TO NON-ZERO TO INDICATE CARDS BEING PUNCHED	5
K(31)=N	6
NNODES=K(4)	7
FC(19)=10000.	8
WRITE(6,101)	9
PUNCH 100, NNODES,(T(I),I=1,NNODES)	10
100 FORMAT(18,9F8.1/(10F8.1))	11
101 FORMAT(36HL TEMPERATURE CARDS BEING PUNCHED)	12
RETURN	13
END	14

APPENDIX H

SYMBOLS USED IN ANALYSIS

A	area, ft^2 ; m^2
ΔA	incremental area, ft^2 ; m^2
A_x	incremental area in x direction in finite difference equation, ft^2 ; m^2
A_y	incremental area in y direction in finite difference equation, ft^2 ; m^2
A_z	incremental area in z direction in finite difference equation, ft^2 ; m^2
a	major semi-axis of tank plus shield, ft; m
$A_i F_{i,j}$	product of i^{th} surface area times geometric radiation view factor between i^{th} and j^{th} surface, ft^2 ; m^2
b	minor semi-axis of tank plus shield, ft; m
C_p	specific heat, $\text{Btu}/(\text{lb})(^{\circ}\text{R})$; $\text{J}/(\text{kg})(\text{K})$
$F_{i,j}$	geometric radiation view factor - portion of total energy, either emitted or reflected diffusely from surface i , that is intercepted by surface j
G	conductor value for heat transfer, $\text{Btu}/(\text{lb})(^{\circ}\text{F})$; $\text{J}/(\text{sec})(\text{K})$
h	tank-to-payload spacing, ft; m
k	thermal conductivity, $\text{Btu}/(\text{hr})(\text{ft})(^{\circ}\text{R})$; $\text{J}/(\text{sec})(\text{m})(\text{K})$
ΔL	payload ring width, ft; m
m_{N_1}	slope of normal N_1
N	normal to center of an incremental surface
N_E	number of surfaces in radiation enclosure
N_J	number of incremental areas in j^{th} payload ring
Q	heat flow, Btu/hr ; J/sec
q	incremental heat flows, either across a plane of any segment or into (or out of) any surface segment, Btu/hr ; J/sec
\dot{q}	internal heat generation rate at each node, Btu/hr ; J/sec
R	distance between any two incremental surfaces, ft; m
R_p	payload radius, ft; m
R_1	distance from tank center to incremental surface, ft; m

R_2	distance from payload center to incremental surface, ft; m
S	source term, $\dot{q}\alpha/k$, $(ft^3)(^0R)/hr$; $(m^3)(K)/sec$
ΔS	thickness of MLI, ft; m
T	temperature, 0R ; K
t	time, sec
V	volume, ft^3 ; m^3
x, y, z	coordinate system, point coordinates
x_r	major semi-axis of tank, ft; m
Δx	incremental distance in x direction
y_r	minor semi-axis of tank, ft; m
Δy	incremental distance in y direction, ft; m
Δz	incremental distance in z direction, ft; m
α	thermal diffusivity, ft^2/hr ; m^2/sec
β	angle measured from minor axis to segment boundary on tank
γ	location angle on payload
ϵ	emissivity
θ	angle on tank to specify segments
ρ	density, lb/ft^3 ; kg/m^3
φ	angle between the normal to a surface and the vector R from that surface
ψ_m	angle from top of tank to R_1

Subscripts:

i	index or counter
j	index or counter
k	index or counter
lat	lateral
m, n	reference or index
$norm$	normal
p	refers to payload surface increment
t	refers to tank surface increment

Notation:

\vec{v} vector

\hat{v} unit vector

∇^2 Laplacian operator, $\frac{\partial^2}{\partial x^2} + \frac{\partial^2}{\partial y^2} + \frac{\partial^2}{\partial z^2}$

$\hat{i}, \hat{j}, \hat{k}$ unit vectors in x, y, z directions

REFERENCES

1. Johnson, William R.; and Cowgill, Glenn R.: A Thermal Analysis of Customized Multilayer Insulation on an Unshrouded Liquid Hydrogen Tank. NASA TN D-6255, 1971.
2. Lewis, D. R.; Gaski, J. D.; and Thomson, L. R.: Chrysler Improved Numerical Differencing Analyzer for Third Generation Computers. Rep. TN-AP-67-287, Chrysler Corp. (NASA CR-99595), Oct. 20, 1967.
3. Howell, John R.; and Siegel, Robert: Thermal Radiation Heat Transfer. Vol. II - Radiation Exchange Between Surfaces and in Enclosures. NASA SP-164, 1969.




Figure 1. - Vehicle configuration.




Figure 2. - Cross-sectional view of model.




Figure 3. - 45° segment of the multilayer insulation (MLI) divided into nodes.




Figure 4. - Cross-sectional view of several nodes.




Figure 6. - Geometric configuration for determining radiation view factors between tank and payload.




Figure 5. - Enclosure for radiation exchange.

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

WASHINGTON, D.C. 20546

OFFICIAL BUSINESS

PENALTY FOR PRIVATE USE \$300

FIRST CLASS MAIL

03U 001 33 51 3DS 71.10 00903
AIR FORCE WEAPONS LABORATORY /WLOL/
KIRTLAND AFB, NEW MEXICO 87117



POSTAGE AND FEES PAID
NATIONAL AERONAUTICS AND
SPACE ADMINISTRATION

ATT E. LOU BOWMAN, CHIEF, TECH. LIBRARY

POSTMASTER: If Undeliverable (Section 158
Postal Manual) Do Not Return

"The aeronautical and space activities of the United States shall be conducted so as to contribute . . . to the expansion of human knowledge of phenomena in the atmosphere and space. The Administration shall provide for the widest practicable and appropriate dissemination of information concerning its activities and the results thereof."

— NATIONAL AERONAUTICS AND SPACE ACT OF 1958

NASA SCIENTIFIC AND TECHNICAL PUBLICATIONS

TECHNICAL REPORTS: Scientific and technical information considered important, complete, and a lasting contribution to existing knowledge.

TECHNICAL NOTES: Information less broad in scope but nevertheless of importance as a contribution to existing knowledge.

TECHNICAL MEMORANDUMS: Information receiving limited distribution because of preliminary data, security classification, or other reasons.

CONTRACTOR REPORTS: Scientific and technical information generated under a NASA contract or grant and considered an important contribution to existing knowledge.

TECHNICAL TRANSLATIONS: Information published in a foreign language considered to merit NASA distribution in English.

SPECIAL PUBLICATIONS: Information derived from or of value to NASA activities. Publications include conference proceedings, monographs, data compilations, handbooks, sourcebooks, and special bibliographies.

TECHNOLOGY UTILIZATION PUBLICATIONS: Information on technology used by NASA that may be of particular interest in commercial and other non-aerospace applications. Publications include Tech Briefs, Technology Utilization Reports and Technology Surveys.

Details on the availability of these publications may be obtained from:

SCIENTIFIC AND TECHNICAL INFORMATION OFFICE

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

Washington, D.C. 20546